

Solid Semiconductor Element, Ink Tank, Ink Jet
Recording Apparatus Provided with Ink Tank, Liquid
Information Acquiring Method and Liquid Physical
Property Change Discriminating Method

5

BACKGROUND OF THE INVENTION

Field of the Invention

10 The present invention relates to a semiconductor
element having a function of detecting environmental
information, and transmitting/displaying the
information to the outside or adjusting environment
based on the information, and methods of using this
semiconductor element to acquire liquid information and
discriminate a physical property change of a liquid.

15 Moreover, the present invention relates to an
apparatus having a function of detecting ink tank
inside information (e.g., ink residual amount,
pressure, and the like), and transmitting/displaying
the information to the outside, an apparatus having a
20 function of adjusting environment based on the
information, an ink tank provided with the elements,
and ink jet recording apparatuses with the ink tank
detachably attachable thereto, such as a facsimile
machine, printer and copying machine.

25 Related Background Art

In a conventional ink jet recording apparatus for
ejecting an ink via a plurality of jet nozzles disposed

in a recording head, scanning a carriage with the recording head mounted thereon with respect to a sheet, and forming an image in a dot pattern, an ink tank with the recording ink contained therein is disposed, and
5 the ink of the ink tank is supplied to the recording head via an ink supply path. Here, an ink residual amount detection apparatus for detecting a residual amount of the ink of the ink tank is brought to practical use, and various proposals have been
10 presented.

For example, as shown in FIG. 1, an apparatus disclosed in Japanese Patent Application Laid-Open No. 6-143607 includes two (pair) of electrodes 702 disposed on an inner bottom surface of an ink tank 701 filled
15 with a nonconductive ink, and a float member 703 floating on an ink surface in the ink tank 701. Two electrodes 702 are connected to a detector (not shown) for detecting a conductive state between the electrodes. Moreover, on the float member 703, an
20 electrode 704 is disposed opposite to the electrode 702. When the ink in the ink tank 701 is consumed, a position of the float member 703 is lowered, and the electrode 704 contacts the electrodes 702. Then, the detector detects the conductive state between the
25 electrodes 702. Thereby, it is detected that there is no ink in the ink tank 701, and an operation of an ink jet recording head 705 is stopped.

Moreover, according to Japanese Patent No. 2947245, an ink jet printer ink cartridge 805 is disclosed. As shown in FIG. 2, a lower portion of the cartridge is formed in a funnel shape toward a bottom surface thereof, two conductors 801, 802 are disposed on the bottom surface, and a metal ball 804 whose specific weight is smaller than that of an ink 803 is disposed in the cartridge. In this constitution, when the ink 803 is consumed and reduced, the liquid surface of the ink 803 is lowered. Accordingly, the position of the metal ball 804 floating on the surface of the ink 803 is lowered. When the liquid surface of the ink 803 is lowered to reach the bottom surface of an ink cartridge housing, the metal ball 804 contacts two conductors 801, 802. Then the conductors 801, 802 become conductive and a current flows therebetween. When the flowing current is detected, an ink end state can be detected. When the ink end state is detected, a user is notified of information indicating the ink end state.

In either one of the aforementioned constitutions, absence of the ink is detected by detecting whether or not there is conduction between the electrodes disposed in the ink tank. Therefore, it is necessary to dispose a detecting electrode in the ink tank. Additionally, while the ink exists in the ink tank, the current is prevented from flowing between the electrodes via the

ink. Therefore, a metal ion cannot be used in an ink component, or another restriction is imposed on the ink for use.

Moreover, in the aforementioned constitution, only
5 the presence/absence of the ink can be detected, and other tank inside information cannot be notified to the outside. For example, an ink residual amount, pressure information in the ink tank, ink physical property change, and the like are important parameters for
10 constantly operating an ink jet head with a stable discharge amount. There is a demand for a tank by which an outside ink jet recording apparatus is notified of a tank inner pressure constantly changing with ink consumption in the tank in real time, or the
15 change of the ink physical properties can be transmitted to the outside.

Furthermore, there is a demand for an ink tank by which the detected information in the ink tank is one-directionally transmitted to the outside, and
20 additionally the inner information can bidirectionally be exchanged in response to a request from the outside.

In order to develop the aforementioned ink tank, the present inventor et al. have noted a ball semiconductor, manufactured by Ball Semiconductor Co.,
25 Ltd., for forming a semiconductor integrated circuit on a spherical surface of a silicon ball with a diameter of 1 mm. This ball semiconductor has a spherical

shape. Therefore, when the semiconductor is contained in the ink tank, the detection of the environmental information and the bi-directional exchange of the information with the outside can expectedly efficiently
5 be performed as a planar shape. However, when the semiconductor having such function is searched, only a technique of connecting the ball semiconductors with each other via an electric wiring, and the like are found (see U.S. Patent No. 5877943). It is therefore
10 necessary to develop an element itself which has the aforementioned function. Moreover, in order to effectively apply the element to the ink tank, there are some inherent problems.

First, a power for activating the element
15 contained in the tank is supplied. When a power source for starting the element is disposed in the ink tank, the tank is enlarged in size. Even when the power source is disposed outside the tank, means for connecting the power source to the element is
20 necessary. A tank manufacturing cost increases, a tank cartridge becomes expensive, and the element has to be started from the outside in a non-contact manner.

Secondly, the element sometimes has to float on the ink surface of the ink tank or in the ink at a
25 given distance from the liquid surface. For example, in order to monitor a fluctuation of a negative pressure amount with time with the ink consumption in

the ink tank, the element is preferably positioned on the ink surface. However, since the element is formed of silicon having a specific weight larger than that of water, it is generally difficult to float the element in the ink.

Thirdly, in a color printer, it is requested to individually and independently obtain respective ink tank inside information in response to an inquiry from the outside for respective color ink tanks and transmit the information.

Fourthly, in one mode of the tank for the ink jet head for practical use, a container is divided into a first chamber in which a porous or fibrous negative pressure generating member for generating a desired negative pressure with respect to the ink jet recording head is contained in an atmosphere connection state, and a second chamber in which a recording liquid is contained as it is. A connection path is disposed in a bottom portion of a wall for partitioning the first and second chambers in the container. This tank has a large ink storage amount and can advantageously stabilized the negative pressure with respect to the ink jet recording head as compared with a tank constituted only of the chamber in which the negative pressure generating member is contained. Therefore, there is a demand especially for an ink tank having a function such that the information such as the ink

residual amount in the tank, ink physical property change, and inner pressure state can bidirectionally be exchanged with the outside in the aforementioned tank structured of two chambers.

5

SUMMARY OF THE INVENTION

9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218

present invention is to provide a method of setting an optimum head driving condition and keeping a stable discharge property.

5 Additionally, an object of the present invention is to provide a liquid container provided with a solid semiconductor element in which liquid chemical physical properties information (pH change, concentration change, density change) and physical properties information (liquid viscosity, surface tension,
10 negative pressure amount) are detected, detected information can bidirectionally be exchanged with the outside, and a tank inner state can be adjusted (negative pressure adjustment), and a liquid discharge recording apparatus provided with the liquid container.

15 To achieve the aforementioned objects, according to the present invention, there is provided a solid semiconductor element disposed in contact with a liquid, the element comprising:

information acquiring (communicating) means for
20 acquiring liquid chemical property information including at least one of a hydrogen ion concentration index, a concentration, and a density of the liquid;

information transmission means for displaying or transmitting the information acquired by the
25 information acquiring means to the outside; and

energy converting means for converting an energy applied from the outside to an energy of a type

different from the type of the applied energy to operate the information acquiring means and the information transmission means.

5 The solid semiconductor element of the present invention is disposed in contact with the liquid as an object from which the information is to be acquired. In this state, the information acquiring means acquires the information about the liquid, and the information transmission means transmits the information to the outside. The energy for operating the information acquiring means and information transmission means is obtained by converting the energy from the outside to the different type of energy by the energy converting means. Since the solid semiconductor element has a function of acquiring the information about the liquid and transmitting the information to the outside in this manner, the information can three-dimensionally be acquired and transmitted. Therefore, as compared with use of a planar semiconductor element, since little restriction is imposed on a direction of acquirement and transmission of the information, the information about the liquid can efficiently be acquired and transmitted to the outside.

25 The element further comprises information storing means for storing information to be compared with the acquired information, and discrimination means for comparing the information stored in the information

storing means with the information acquired by the information acquiring means to discriminate a need for transmission of the information to the outside.

Therefore, the acquired information is transmitted to the outside if necessary. Furthermore, when receiving means for receiving a signal from the outside is added, the information is acquired in response to the received signal, a result of the comparison with the stored information is transmitted to the outside together with the acquired information, and the signal can bidirectionally be transmitted/received with respect to an outside apparatus.

Examples of the information about the liquid include a pH and pressure of the liquid, and particularly include a residual amount of the liquid in the container when the liquid is contained in the container. To obtain the liquid residual amount, the solid semiconductor element is preferably disposed to float on a liquid surface or in the liquid, and the constitution may also include a hollow portion.

The solid semiconductor element of the present invention is preferably used to obtain the information about a recording ink in a field of ink jet recording. The recording ink is generally contained in the ink tank. It is very important to obtain the information about the ink in the ink tank when a high-quality recording is performed.

Therefore, the ink tank of the present invention contains the ink to be supplied to a discharge head for discharging the ink, and the solid semiconductor element of the present invention is disposed to contact the ink. The number of solid semiconductor elements may be one or plural. When a plurality of solid semiconductor elements are disposed, the respective elements may acquire different information, or exchange the information with one another.

Moreover, according to the present invention there is provided an ink tank which contains an ink to be supplied to an ejection head for ejecting the ink, the ink tank comprising:

information acquiring means for acquiring ink chemical property information including at least one of a hydrogen ion concentration index, a concentration, and a density of the ink;

information transmission means for displaying or transmitting the information acquired by the

information acquiring means to the outside; and

energy converting means for converting an energy applied from the outside to an energy of a type different from the type of the applied energy to operate the information acquiring means and the information transmission means.

An ink jet recording apparatus of the present invention is provided with an ejection head for

ejecting an ink, and the ink tank of the present invention in which the ink to be supplied to the ejection head is contained.

According to the present invention, there is
5 provided a liquid change information acquiring method of using a solid semiconductor element disposed in contact with a liquid, the element comprising:

information acquiring means for acquiring
information about the liquid;

10 information transmission means for displaying or transmitting the information acquired by the information acquiring means to the outside; and

energy converting means for converting an energy
applied from the outside to an energy of a type
15 different from the type of the applied energy to operate the information acquiring means and the information transmission means.

Furthermore, according to the present invention there is provided a liquid physical property change
20 judging method of using a solid semiconductor element disposed in contact with a liquid, the element comprising:

information acquiring means for acquiring
information about the liquid;

25 discrimination means for discriminating a liquid physical property change based on the information acquired by the information acquiring means and a pre-

stored data table;

information transmission means for displaying or transmitting the information acquired by the discrimination means to the outside; and

5 energy converting means for converting an energy applied from the outside to an energy of a type different from the type of the applied energy to operate the information acquiring means, the discrimination means and the information transmission
10 means.

According to the aforementioned method, the liquid physical property change can be detected with time. For example, when a disadvantage is possibly generated by the use, this is notified to the outside to restrict
15 the use. Particularly for use in the ink tank, a viscosity and surface tension change amount of the ink as the liquid are estimated, and an optimum recording head driving condition can be set.

Furthermore, according to the present invention,
20 there is provided a discriminating method of acquiring information about a liquid with time, and estimating a change amount of the liquid from information indicating a change of the information about the liquid with time,
wherein abnormal change information about the
25 liquid is discriminated.

For example, the amount of the ink contained in the ink tank usually linearly decreases with

consumption, but rapidly increases because of replenishment, or an ink component changes. This can be judged as abnormal change information according to the method.

5 To achieve the aforementioned objects, according to the present invention, there is provided a solid semiconductor element comprising: receiving and energy converting means for receiving a signal of an electromagnetic wave from the outside in a non-contact
10 manner, and converting the electromagnetic wave to a power by electromagnetic induction; information acquiring means for acquiring outside environmental information; information storing means for storing information to be compared with the information
15 acquired by the information acquiring means; discrimination means for comparing the information acquired by the information acquiring means with the corresponding information stored in the information storing means to discriminate a need for information
20 transmission when the signal of the electromagnetic wave received by the receiving and energy converting means satisfies a predetermined response condition; and information transmission means for displaying or transmitting the information acquired by the
25 information acquiring means to the outside when the discrimination means discriminates the need for the information transmission. The information acquiring

means, the information storing means, the discrimination means, and the information transmission means are operated by the power converted by the receiving and energy converting means.

5 An electromagnetic induction frequency or a communication protocol can be applied as the response condition.

10 For the information transmission means, the power converted by the receiving and energy converting means is supposedly converted to a magnetic field, a light, a shape, a color, a radio wave, or a sound as the energy for displaying or transmitting the information to the outside.

15 The receiving and energy converting means having a conductor coil and oscillation circuit for generating the power with an outside resonance circuit by electromagnetic induction can be applied.

20 In this case, the conductor coil is formed to be wound around an outer surface of the solid semiconductor element.

25 Moreover, the element preferably comprises a hollow portion for floating the element on a liquid surface or in a predetermined position in the liquid. In this case, a gravity center of the solid semiconductor element floating in the liquid is positioned below a center of the element. The floating element preferably rocks stably without rotating in

the liquid. A metacenter of the solid semiconductor element is preferably constantly positioned above the gravity center of the solid semiconductor element.

Furthermore, according to the present invention
5 there is provided an ink tank in which at least one of solid semiconductor element is disposed.

In this case, the response condition of the solid semiconductor element preferably differs with the ink in the tank. Concretely, the response condition of the
10 solid semiconductor element differs with an ink color, a color material concentration, or a physical property in the ink tank.

Additionally, according to the present invention,
15 there is provided an ink jet recording apparatus in which a plurality of ink tanks are disposed.

In this case, the ink jet recording apparatus preferably comprises communication means for transmitting/receiving an electromagnetic wave with respect to the solid semiconductor element in each ink
20 tank. Furthermore, the communication means having a resonance circuit for emitting the electromagnetic wave can be applied.

Moreover, according to the present invention,
25 there is provided a communication system in which a solid semiconductor element is used, comprising: a plurality of liquid containers in which the respective solid semiconductor elements are disposed; an

oscillation circuit formed in the solid semiconductor element and provided with a conductor coil; information acquiring means for acquiring the information in the container; receiving means for receiving a signal from the outside; information transmission means for transmitting the information to the outside when a predetermined response condition is satisfied; an outside resonance circuit, disposed outside the plurality of liquid containers, for generating a power with respect to the oscillation circuit of the solid semiconductor element by electromagnetic induction; and outside communication means for bidirectionally communicating with the receiving means and the information transmission means of the solid semiconductor element.

In this case, the response condition allows the electromagnetic induction frequency or the communication protocol to differ with each container.

Furthermore, the gravity center of the solid semiconductor element floating in the liquid is positioned below the center of the element. The floating element preferably rocks stably without rotating in the liquid. The metacenter of the solid semiconductor element is preferably constantly positioned above the gravity center of the solid semiconductor element.

As described above, when the signal of the

electromagnetic wave is applied to the solid
semiconductor element from the outside in the non-
contact manner, the receiving and energy converting
means converts the electromagnetic wave to the power,
5 and the information acquiring means, discrimination
means, information storing means, and information
transmission means are started by the converted power.
The discrimination means allows the information
acquiring means to acquire element environmental
10 information when the signal of the electromagnetic wave
received by the receiving and energy converting means
satisfies the predetermined response condition,
compares the acquired information with the
corresponding information stored in the information
15 storing means, and discriminates the need for
information transmission. Moreover, when it is judged
that the information transmission is necessary, the
discrimination means allows the information
transmission means to transmit the acquired information
20 to the outside.

In this manner, since the solid semiconductor
element has the communication function of acquiring the
environmental information and transmitting the
information to the outside only when the signal of the
25 electromagnetic wave from the outside satisfies the
predetermined response condition, the environmental
information of the respective elements are

independently acquired. Moreover, since the information can three-dimensionally be acquired/transmitted, the direction of the information transmission is little restricted as compared with the use of the planar semiconductor element. Therefore, the environmental information can efficiently be acquired and transmitted to the outside.

Moreover, since at least one solid semiconductor element is disposed in the ink tank, the information about the ink contained in the ink tank, pressure in the tank, and the like can be transmitted to the outside, for example, to the ink jet recording apparatus in real time. This is advantageous, for example, in stabilizing ink jet ejection by controlling the negative pressure amount in the tank, which changes with ink consumption every moment.

Particularly, for the plurality of ink tanks with the respective solid semiconductor elements disposed therein, only when the received electromagnetic wave signal satisfies the predetermined response condition, the information is acquired in response to the received signal, and a result of comparison/discrimination with the stored information is transmitted to the outside together with the acquired information. Therefore, when the response condition is changed for each tank, the information for the respective ink tanks can independently be obtained. Therefore, a user can

replace the ink tank in which the ink is used up without mistake.

Furthermore, the power for operating the solid semiconductor element is supplied in the non-contact manner in the constitution. Therefore, it is unnecessary to dispose a power source for starting the element in the ink tank or to connect a power supplying wiring to the element. The constitution can be used in a place where it is difficult to dispose a wiring directly connected to the outside.

For example, when the conductor coil of the oscillation circuit is formed to be wound around the outer surface of the solid semiconductor element, the power is generated in the conductor coil by electromagnetic induction with respect to the outside resonance circuit, and the power can be supplied to the element in the non-contact manner.

In this case, since the coil is wound around the outer surface of the element, a size of inductance of the coil changes in accordance with an ink residual amount, ink concentration, and ink pH in the ink tank. Therefore, since an oscillation frequency of the oscillation circuit is changed in accordance with the inductance change, the ink residual amount, and the like in the ink tank can also be detected based on the change of the oscillation frequency.

Moreover, since the solid semiconductor element

has the hollow portion for floating in the liquid and the gravity center of the element is positioned below the center of the element, for example, the recording head and ink tank mounted on the ink jet recording apparatus serially operate. Even when the ink in the ink tank vertically and horizontally rocks, the element floats steadily in the ink in the ink tank, and the information about the ink, pressure in the tank, and the like can precisely be detected. Additionally, the coil of the oscillation circuit formed on the element is held in a stable position with respect to the coil of the outside resonance circuit, and stable bidirectional communication is also constantly enabled.

Moreover, according to the present invention, there is provided a liquid container in which an ink to be supplied to a liquid ejection head for ejecting a liquid droplet is contained, the liquid container comprising: a first chamber which is partially connected to atmosphere and in which an absorber for absorbing a liquid is contained; a second chamber which is closed from the outside and in which the liquid is contained; a connection path, disposed in the vicinity of a bottom portion of the container, for connecting the first chamber to the second chamber; and a supply port which is disposed in the first chamber, and via which the liquid is supplied to the liquid ejection head. First monitor means for monitoring a liquid

amount of the first chamber is disposed in the first chamber. A flow rate adjustment apparatus for adjusting a flow rate of the connection path in accordance with information from the first monitor means is disposed in the connection path.

In this case, second monitor means for monitoring the liquid amount of the second chamber is disposed in the second chamber, and the flow rate adjustment apparatus is preferably controlled in accordance with the information from the second monitor means.

As the first monitor means, a first solid semiconductor element is preferably used which comprises: pressure detection means for detecting a pressure fluctuation of the liquid; information transmission means for transmitting pressure information obtained by the pressure detection means to the flow rate adjustment apparatus; and energy converting means for converting an energy applied from the outside to an energy different from the applied energy to operate the pressure detection means and the information transmission means. The solid semiconductor element requires no power wiring, and can freely be disposed in any position without being restricted.

Particularly, the first solid semiconductor element is preferably disposed above a liquid surface of the first chamber when a liquid supply to the first

chamber from the second chamber is possibly interrupted, and in a position in which the fluctuation of the pressure can be detected. When the element is disposed in such position, the interruption of the liquid supply can be detected beforehand.

The flow rate adjustment apparatus is preferably a second solid semiconductor element which comprises: at least receiving means for receiving the pressure information from the first monitor means; an open/close valve which operates in response to the received pressure information; and energy converting means for converting an energy applied from the outside to an energy different from the applied energy to operate the receiving means and the open/close valve. Because no power wiring is required, and the element can be disposed even in a narrow position.

Moreover, the second monitor means is preferably a third solid semiconductor element which comprises: at least residual amount detection means for detecting a liquid residual amount; information transmission means for transmitting residual amount information obtained by the residual amount detection means to the flow rate adjustment apparatus; and energy converting means for converting an energy applied from the outside to an energy different from the applied energy to operate the residual amount detection means and the information transmission means. Because the element can be

disposed without requiring any power wiring.

Furthermore, according to the present invention, there is provided a liquid ejection recording apparatus comprising: a liquid ejection head for ejecting a
5 recording liquid droplet; and a liquid container in which the liquid to be supplied to the liquid ejection head is contained. In this case, the liquid ejection head preferably ejects the liquid droplet via a nozzle utilizing a film boiling caused when the heat energy is
10 applied to the liquid. However, the present invention is not limited to the aforementioned mode. In another mode of the liquid ejection head of the present invention, an electric signal is inputted to a thin film element, the thin film element is minutely
15 displaced, and the liquid is ejected via the nozzle.

Additionally, the "metacenter" described herein indicates an intersection of an action line of a balanced weight with an action line of a buoyancy during tilting.

20 Moreover, examples of a "solid shape" of the "solid semiconductor element" include various cubical shapes such as a triangle pole, sphere, hemisphere, square pole, rotary ellipse, and uniaxial rotator.

25 BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a diagram showing one example of a conventional ink residual amount detection apparatus.

FIG. 2 is a diagram showing another example of the conventional ink residual amount detection apparatus.

FIG. 3 is a block diagram showing an inner constitution of a solid semiconductor element according to a first embodiment of the present invention and an exchange of the element with the outside.

FIG. 4 is a flowchart showing an operation of the solid semiconductor element shown in FIG. 3.

FIG. 5 is an explanatory view showing a power generation principle of energy converting means as a constituting element of the solid semiconductor element of the present invention.

FIG. 6 is a schematic view of an ink tank in which the solid semiconductor element shown in FIG. 3 is contained.

FIG. 7 is a diagram showing an output from an oscillation circuit shown in FIG. 5 in a relation between resonance frequency and amplitude.

FIGS. 8A and 8B are diagrams showing a relation between a peak value of the output amplitude from the oscillation circuit shown in FIG. 5 and pH of an ink.

FIGS. 9A, 9B, 9C, 9D, 9E, 9F and 9G are diagrams showing a series of steps according to one example of a manufacturing method of a floating solid semiconductor element shown in FIG. 6.

FIG. 10 is a schematic longitudinal sectional view showing an N-MOS circuit element for use in the solid

semiconductor element of the present invention.

FIG. 11 is a block diagram showing the inner constitution of the solid semiconductor element according to a second embodiment of the present invention and the exchange of the element with the outside.

FIG. 12 is a flowchart showing the operation of the solid semiconductor element shown in FIG. 11.

FIG. 13 is a block diagram showing the inner constitution of the solid semiconductor element according to a third embodiment of the present invention and the exchange of the element with the outside.

FIGS. 14A and 14B are diagrams showing a position of the element floated in the ink of the ink tank and constituted as shown in FIG. 11, together with an ink consumption change.

FIG. 15 is a flowchart for checking the position of the element having the constitution shown in FIG. 11, and judging a need for tank replacement.

FIGS. 16A, 16B and 16C are explanatory views showing a concept of a fourth embodiment of the present invention.

FIG. 17 is a diagram showing an example in which the solid semiconductor element constituted by appropriately combining the first, second and third embodiments is disposed in the ink tank and an ink jet

head connected to the tank.

FIG. 18 is a diagram showing a constitution
example in which an electromotive force supplied to a
certain solid semiconductor element is successively
5 transmitted to another solid semiconductor element
together with the information in the ink tank and
connected ink jet head.

FIG. 19 is an explanatory view of an ion sensor as
one example of information acquiring means constituting
10 the solid semiconductor element of the present
invention.

FIGS. 20A and 20B are explanatory views of an
associated state of dye ion in the ink.

FIGS. 21A and 21B are diagrams showing one example
15 of a circuit for outputting a detection result in the
ion sensor shown in FIG. 19.

FIG. 22 is a diagram showing an example of the
preferred ink tank in which the solid semiconductor
element is disposed according to various embodiments of
20 the present invention.

FIG. 23 is a diagram showing an example of the
preferred ink tank in which the solid semiconductor
element is disposed according to various embodiments of
the present invention.

25 FIG. 24 is a diagram showing an example of the
preferred ink tank in which the solid semiconductor
element is disposed according to various embodiments of

the present invention.

FIG. 25 is a diagram showing an example of the preferred ink tank in which the solid semiconductor element is disposed according to various embodiments of the present invention.

FIG. 26 is a schematic perspective view showing one example of an ink jet recording apparatus on which the ink tank provided with the solid semiconductor element of the present invention is mounted.

FIGS. 27A and 27B are explanatory views showing a condition for holding a stable state of the solid semiconductor element manufactured in the method shown in FIGS. 9A to 9G in the liquid.

FIG. 28 is an explanatory view showing one example of a structure of a pressure sensor disposed in the solid semiconductor element of the present invention.

FIG. 29 is a circuit diagram of a circuit for monitoring an output from a polysilicon resistance layer shown in FIG. 28.

FIG. 30 is a sectional view of a water tube in which the solid semiconductor element of the present invention is disposed.

FIG. 31 is a schematic sectional view of a micro valve in which the solid semiconductor element of the present invention is disposed.

FIGS. 32A and 32B are explanatory views showing an operation of the micro valve shown in FIG. 31.

FIG. 33 is a schematic sectional view of an ink jet device to which the micro valve shown in FIG. 31 is applied.

FIG. 34 is a schematic constitution diagram showing the ink jet recording apparatus according to a fifth embodiment of the present invention.

FIG. 35 is a diagram showing a conductor coil wound around a surface of the solid semiconductor element of the present invention to constitute receiving and energy converting means.

FIG. 36 is a block diagram showing the inner constitution of the solid semiconductor element of the present invention and the exchange of the element with the outside.

FIG. 37 is an explanatory view of a concept by which digital ID is exchanged between an apparatus main body and the solid semiconductor element in the tank by electromagnetic induction in the ink jet recording apparatus according to a sixth embodiment of the present invention.

FIG. 38 is a diagram showing an operation flow for using the exchange of the digital ID shown in FIG. 37 to acquire tank inside information of a specific color.

FIG. 39 is a block diagram showing the inner constitution of the solid semiconductor element according to one embodiment of the present invention and the exchange of the element with the outside.

FIG. 40 is a schematic constitution diagram of the ink tank using the solid semiconductor element of the present invention.

FIG. 41 is a graph showing an absorption
5 wavelength of an representative ink (yellow, magenta, cyan, black).

FIG. 42 is a schematic sectional view showing a seventh embodiment of the ink tank of the present invention.

10 FIG. 43 is an explanatory view of one example of the pressure valve structure of the solid semiconductor element disposed in the connection path of the ink tank of FIG. 42.

15 FIGS. 44A, 44B, 44C, 44D, 44E, 44F and 44G are explanatory views of manufacturing steps of the pressure valve shown in FIG. 43.

FIG. 45 is a plan view of the solid semiconductor element in a state shown in FIG. 44F.

20 FIG. 46 is an equivalent circuit diagram of an electric constitution of the pressure valve shown in FIG. 43.

25 FIG. 47 is a timing chart of one example of an applied signal to a valve electrode and base electrode in the pressure valve shown in FIG. 46.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Embodiments of the present invention will be

described hereinafter with reference to the drawings. Particularly, the embodiment in which respective solid semiconductor elements are disposed in respective color ink tanks will be described in detail. Additionally,
5 the element is not contained only in the ink tank. Even when the element is disposed and used in another object, a similar effect is obtained.

(First Embodiment)

FIG. 3 is a block diagram showing an inner
10 constitution of the solid semiconductor element according to a first embodiment of the present invention and an exchange of the element with the outside. A solid semiconductor element (hereinafter referred to only as an "element" 11 shown in FIG. 3 is
15 disposed in an ink tank, and includes energy converting means 14 for converting an electromotive force 12 supplied to the element 11 from an outside A to a power 13, information acquiring means 15 started by the power 13 converted by the energy converting means 14,
20 discrimination means 16, information storing means 17, and information communicating electromagnetic induction, heat, light, ray, and the like can be applied to the electromotive force supplied to operate the element 11. Moreover, at least the energy
25 converting means 14 and information acquiring means 15 are preferably formed on the surface of the element 11 or in the vicinity of the surface.

The information acquiring means 15 acquires information (ink information) about the ink in the ink tank as environmental information of the element 11, and outputs the information to the discrimination means 5 16. The discrimination means 16 compares the ink information obtained from the information acquiring means 15 with information stored in the information storing means 17, and judges whether or not it is necessary to transmit the acquired ink information to 10 the outside. The information storing means 17 stores various conditions for comparison with the obtained ink information and ink information itself obtained from the information acquiring means 15 as a data table. The information communicating means 18 converts the 15 power applied by the energy converting means 14 to an energy for transmitting the ink information to the outside A or an outside B, and transmits the ink information to the outside A or B based on a command from the discrimination means 16. Here, the outside B 20 is an object different from the outside A as a supply source of the electromotive force 12, and includes an ink jet recording apparatus on which the ink tank with the element 11 contained therein is mounted, and additionally organs of human senses of sight and 25 hearing.

FIG. 4 is a flowchart showing an operation of the element shown in FIG. 3. Referring to FIGS. 3 and 4,

when the electromotive force 12 is applied to the element 11 from the outside A, the energy converting means 14 converts the electromotive force 12 to the power 13, and the information acquiring means 15, discrimination means 16, information storing means 17, and information communicating means 18 are started by the power 13.

The started information acquiring means 15 acquires the ink information in the ink tank as the environmental information of the element 11, such as an ink residual amount, ink type, temperature, and pH (step S11 of FIG. 4). Subsequently, the discrimination means 16 reads a condition for referring to the acquired tank inside information from the information storing means 17 (step S12 of FIG. 4), and compares the read condition with the acquired tank inside information, and discriminates a need for information transmission (step S13 of FIG. 4). Here, for discrimination based on the condition preset in the information storing means 17, for example, the need for tank replacement is discriminated when a raw ink residual amount is 2 ml or less, or when the ink pH largely changes.

In the step S13, the discrimination means 16 judges that it is unnecessary to transmit the tank inside information to the outside, and the existing ink tank inside information is stored in the information

storing means 17 (step S14 of FIG. 4). Additionally,
when the information acquiring means 15 next acquires
the ink tank inside information, the discrimination
means 16 may compare the acquired information with the
5 stored information.

Moreover, in the step S13, the discrimination
means 16 judges that it is necessary to transmit the
ink tank inside information to the outside, and further
the information communicating means 18 converts the
10 power 13 converted by the information acquiring means
15 to the energy for transmitting the ink tank inside
information to the outside. A magnetic field, light,
shape, color, radio wave, sound, and the like can be
used as the transmitting energy. For example, when it
15 is judged that the ink residual amount is 2 ml or less,
a sound is emitted to transmit the need for tank
replacement to the outside B (e.g., ink jet recording
apparatus) (step S15 of FIG. 4). Moreover, a
transmission destination is not limited to the ink jet
20 recording apparatus, and particularly the light, shape,
color, sound, and the like may be transmitted to the
human senses of sight and hearing. Furthermore, when
it is judged that the raw ink residual amount is 2 ml
or less, the sound is emitted. When the ink pH largely
25 changes, light is emitted. A transmission method may
be changed in accordance with the information in this
manner.

For use in a serial type ink jet recording apparatus, examples of a preferable position in which means for supplying the electromotive force as the outside energy to the element 11 is disposed include a recording head, carriage, recording head recovery position, carriage return position, and the like.

Alternatively, when an apparatus having the means for supplying the electromotive force is used, an inside state of the ink tank can be known without the ink jet recording apparatus. For example, a quality of the ink tank can be tested without actually attaching the ink tank to the ink jet recording apparatus in a factory or a store.

According to the first embodiment, since the element 11 includes the information acquiring means 15, it is unnecessary to connect an electric wiring directly to the outside. The element 11 can be used even in a position in which it is difficult to connect the electric wiring directly to the outside, for example, in the ink as described later with reference to FIG. 13 to FIGS. 16A to 16C or any position in the object. When the element 11 is disposed in the ink, the ink state can accurately be grasped in real time.

Moreover, since the element 11 includes the information acquiring means 15, it is unnecessary to dispose means (power source in the present embodiment) for storing the electromotive force for operating the

element 11 in the element 11. Therefore, the element 11 can be miniaturized, and used even in a narrow position, in the ink as described later with reference to FIG. 13 to FIGS. 16A to 16C, or in any position in the object. Additionally, the electromotive force is supplied to the element 11 in the non-contact manner with respect to the element 11 in the first embodiment. However, after the electromotive force is supplied by temporary contact with the outside, the outside may be disconnected.

Here, for the energy converting means 14, an example in which electromagnetic induction is utilized to generate the power will be described.

FIG. 5 is an explanatory view showing a power generation principle of the energy converting means as a constituting element of the solid semiconductor element of the present invention.

In FIG. 5, an outside resonance circuit 101 having a coil L_a , and oscillation circuit 102 having a coil L are disposed while the opposite coils L_a , L are adjacent to each other. When a current I_a is passed through the coil L_a via the outside resonance circuit 101, a magnetic flux B is generated through the coil L of the oscillation circuit 102 by the current I_a . Here, when the current I_a is changed, the magnetic flux B through the coil L changes, and an induced electromotive force V is generated in the coil L . Therefore, the

oscillation circuit 102 is formed as the energy
converting means in the element 11. For example, in
the ink jet recording apparatus outside the element 11,
the outside resonance circuit 101 is disposed in such a
5 manner that the coil L of the element-side oscillation
circuit 102 is adjacent to the coil L_a of the resonance
circuit 101. Thereby, the power for operating the
element 11 can be generated by the induced
electromotive force by electromagnetic induction from
10 the outside.

Since the magnetic flux B passed through the coil
L of the oscillation circuit 102 formed as the energy
converting means in the element 11 is proportional to a
product of a winding number N_a and current I_a of the
15 outside resonance circuit 101, the magnetic flux is
represented as follows, using a proportional constant
k.

$$B = kN_a I_a \quad (1)$$

Moreover, when the winding number of the coil L is
20 N, the electromotive force V generated in the coil L is
as follows.

$$\begin{aligned}
 V &= -N \frac{dB}{dt} \\
 &= kN_a N \frac{dI_a}{dt} \\
 &= -M \frac{dI_a}{dt} \quad (2)
 \end{aligned}$$

Here, when a permeability of a magnetic center of the coil L is μ_a , magnetic field is H, and a distance between the coil L_a of the outside resonance circuit 101 and the coil L formed in the element 11 is z, the magnetic flux B is represented as follows.

$$\begin{aligned}
 B &= \mu_a H(z) \\
 &= \frac{\mu_a N_a I_a r_a^2}{2(r_a^2 + z^2)^{3/2}} \quad (3)
 \end{aligned}$$

Moreover, a mutual inductance M of the equation (2) is represented as follows.

$$\begin{aligned}
 M &= \frac{\mu N}{\mu_a I_a} \int_s B \cdot dS \\
 &= \frac{\mu \mu_a r_a^2 N_a N S}{2\mu_0 (r_a^2 + z^2)^{3/2}} \quad (4)
 \end{aligned}$$

10

Here, μ_0 is a permeability in vacuum.

Moreover, an impedance Z of the oscillation

circuit 102 formed in the element 11 is represented as follows.

$$Z(\omega) = R + j\left(\omega L - \frac{1}{\omega L}\right) \quad (5)$$

5 An impedance Z_a of the outside resonance circuit 101 is represented as follows.

$$Z_a(\omega_0) = R_a + j\omega L_a - \frac{\omega^2 M^2}{Z(\omega)} \quad (6)$$

Here, J denotes magnetization.

When the outside resonance circuit 101 resonates (current value: I_a is maximized), an impedance Z_0 is
10 represented as follows.

$$Z_0(\omega_0) = R_a + jL_a\omega_a - \frac{\omega_0^2 M^2}{R} \quad (7)$$

A phase delay of ϕ of the oscillation circuit 102 is as follows.

$$\tan\phi = \frac{jL_a\omega_0 - \frac{\omega_0^2 M^2}{R}}{R} \quad (8)$$

15 Furthermore, a resonance frequency f_0 of the outside resonance circuit 101 is obtained by equation (9).

$$f_0 = \frac{1}{2\pi\sqrt{LC}} \quad (9)$$

From the above relation, when the impedance Z of the oscillation circuit 102 formed in the element 11 changes in accordance with the ink change in the ink tank, the frequency of the outside resonance circuit 101 changes, and the ink change is reflected in an amplitude and phase difference of the impedance Z_a of the outside resonance circuit 101. Furthermore, the phase difference and amplitude also include the ink residual amount (i.e., change of Z).

For example, when the resonance frequency f_0 of the outside resonance circuit 101 is changed, the output (impedance Z) from the oscillation circuit 102 formed in the element 11 changes in accordance with an environmental change. Therefore, when dependence on the frequency is detected, the presence/absence of the ink or the ink residual amount can be detected.

Therefore, the oscillation circuit 102 formed in the element 11 serves not only as the energy converting means 14 for generating the power but also as a part of the information acquiring means 15 for detecting the ink change in the ink tank from the relation between the oscillation circuit 102 and the outside resonance circuit 101.

An constitution example of the aforementioned ink tank containing the element 11 to which the power is

supplied from the outside resonance circuit 101 as the element for detecting the ink information will be described with reference to FIG. 6.

FIG. 6 is a schematic view of the ink tank in which the element shown in FIG. 3 is contained. An ink tank 50 shown in FIG. 6 includes a negative pressure generation chamber 51 and ink chamber 52 partitioned from each other via a partition wall 50a. A lower end of the partition wall 50a forms a connection path 50b, and the negative pressure generation chamber 51 is connected to the ink chamber 52 via the connection path 50b. In the negative pressure generation chamber 51, a negative pressure generating member constituted of a fibrous or porous material is contained. The ink is held and absorbed by the negative pressure generating member in the negative pressure generation chamber 51. Moreover, in the negative pressure generation chamber 51, an ink supply port 53 for supplying the ink of the negative pressure generation chamber 51 to the outside such as the ink jet recording apparatus (not shown), and an atmosphere connection port (not shown) for connecting the inside of the negative pressure generation chamber 51 to the atmosphere are disposed. The ink chamber 52 is a substantially closed structure excluding the connection path 50b, and holds the ink as it is, and the element 11 is floated on the liquid surface of the ink held in the ink chamber 52. Such

structure for floating the element 11 will be described later. The oscillation circuit (not shown) described with reference to FIG. 5 is formed in the element 11. The element 11 generates the power by the induced
5 electromotive force generated by the electromagnetic induction from the outside resonance circuit 101 disposed under the ink tank 50, further generates the resonance frequency, and transmits the ink information in the ink tank 50 to the outside. In FIG. 6, a
10 denotes electromagnetic induction, and b denotes oscillation.

According to the ink tank 50 constituted as described above, with ink consumption via the ink supply port 53, gas (gas introduced via the atmosphere
15 connection port) is discharged to the ink chamber 52 from the negative pressure generation chamber 51 via the connection path 50b, and the corresponding amount of ink is introduced to the negative pressure generation chamber 51 from the ink chamber 52.
20 Thereby, the ink amount held in the negative pressure generation chamber 51, that is, the negative pressure in the negative pressure generation chamber 51 is held to be substantially constant.

Here, an example of an output generated by the
25 oscillation circuit disposed in the element 11 is shown as a relation between the resonance frequency and the amplitude in FIG. 7. In FIG. 7, as shown by a to c,

the output generated by the oscillation circuit indicates a difference in the resonance frequency indicating an amplitude peak value and the amplitude in the peak value in accordance with an ink situation in the ink tank 50 (accurately the ink chamber 52).

Concretely, as shown in FIG. 8A, resonance frequencies f_a , f_b , f_c indicating the amplitude peak values have correlation with the ink pH. When the relation shown in FIG. 8A is measured beforehand, the ink pH change can be detected. Also for an ink concentration, a similar relation is seen in a different frequency area band. When the relation is measured beforehand, an ink concentration change can be detected.

Moreover, amplitude value changes A, B, C in a resonance frequency range shown in FIG. 7 have correlation with a distance between the element and the outside resonance circuit 101 as shown in FIG. 8B. Therefore, the amplitude value of a point at which the tank is filled with the ink (F) or at which the tank is empty (E) is measured beforehand. Thereby, the position of the element 11 in the ink tank 50, that is, the ink residual amount can be detected.

Moreover, a liquid density can also be approximated using the following state equation:

$$PV = nRT \quad (10)$$

(Here, P: pressure, V: volume, n: gram molecular weight, R: gas constant, T: absolute temperature).

In the equation (10), when T is constant, density n is represented as follows:

$$\rho = \frac{MP}{nRT} \quad (11)$$

(Here, M: molecular weight). That is, when a liquid
5 pressure and temperature can be detected, a liquid
density state change can also be measured.

The liquid pressure will be described later in
detail. A pressure sensor is constituted by forming a
diaphragm of a polysilicon film, and utilizing a
10 resistance value change with diaphragm displacement
caused by a pressure change, and formed in the element
11 of the first embodiment so that the pressure can be
detected.

Moreover, for the liquid temperature, for example,
15 when a diode sensor, described in Japanese Patent
Application Laid-Open No. 52387/1995, for detecting a
recording head temperature is formed in the element 11
of the first embodiment, the temperature can be
detected.

20 As described above, when the pressure and
temperature sensors are formed in the element 11, the
ink density can be detected. When a change with time
can similarly be detected, a change of a liquid
viscosity/surface tension can also be estimated.

25 For the liquid viscosity, a liquid viscosity

change can be estimated in accordance with a density change from Oriik Arbor equation:

$$\ln \frac{\eta}{\rho M} = A + \frac{B}{T} \quad (12)$$

(Here, η : viscosity, A: constant, B: constant).

5 There is a relation equation by Macleod between the liquid surface tension and density.

$$\gamma = \{C(\rho_0 - \rho)\}^{4.0} \quad (13)$$

(Here, γ : surface tension, C: constant determined by liquid.) the liquid surface tension change can be
10 estimated in accordance with the density change from the equation (13).

As described above, when the element 11 is applied to the ink tank 50, the ink information such as the ink pH, concentration and density can be detected with time
15 and transmitted to the outside of the ink tank 50.

Therefore, for example, when the used ink tank is replaced with another tank, another ink is injected into the ink tank 50, and an ink amount abnormally increases or an ink component changes, these can
20 accurately be detected as abnormalities. Moreover, since the change of the ink viscosity and surface tension can also be estimated, these information are transmitted to a recording head controller, and a driving condition for keeping a stable ejection
25 property can also be set.

Additionally, in FIG. 6, the element 11 having the constitution shown in FIG. 3 is used, but the discrimination means 16 and information storing means 17 may be disposed outside the ink tank 50, not in the element 11.

Additionally, as described above, the element 11 is floated on the ink surface in the ink tank 50 shown in FIG. 6. The element 11 floating on the ink surface will be described hereinafter together with a manufacturing method.

FIG. 9A to 9G are diagrams of a series of steps showing one example of a method of using a spherical silicon as a base of the aforementioned ball semiconductor to manufacture the floating element 11 shown in FIG. 6. Additionally, FIGS. 9A to 9G shows respective steps in a sectional view along a center of the spherical silicon. Moreover, the gravity center of spherical silicon is formed below the center, and an inner upper portion of a sphere is formed to be hollow. Furthermore, the hollow portion is held to be hermetic. The manufacturing method will be described as an example.

First, as shown in FIG. 9B, a thermally oxidized SiO_2 film 202 is formed on the whole surface of a spherical silicon 201 shown in FIG. 9A. Subsequently, when an opening 203 is formed in a part of the SiO_2 film 202 as shown in FIG. 9C, a photolithography process is

used to pattern the film.

Subsequently, as shown in FIG. 9D, an upper half of the spherical silicon 201 is removed by anisotropic etching using a KOH solution via the opening 203, and a hollow portion 204 is formed. Thereafter, as shown in FIG. 9E, an LPCVD process is used to coat a whole exposed surface of the spherical silicon 201 and SiO₂ film 202 including an inner surface of the hollow portion 204 with an SiN film 205.

Furthermore, as shown in FIG. 9F, a metal CVD process is used to form a Cu film 206 on the outer surface of the SiN film 205. Subsequently, as shown in FIG. 9G, a known photolithography process is used to pattern the Cu film 206, and the conductor coil L as a part of the oscillation circuit 102 (see FIG. 3) is formed with the winding number N. Thereafter, the cubical element with the conductor coil L formed thereon is extracted to the atmosphere from the vacuum apparatus, the upper opening 203 is closed by a seal member 207 such as a resin and stopper, and the hollow portion 204 inside the sphere is brought to a sealed state. When the element is manufactured in this manner, the element itself formed of silicon can have buoyancy.

Moreover, an N-MOS circuit element is used in driving circuit elements formed beforehand in the spherical silicon, excluding the coil L, before

manufacturing the floating type solid semiconductor element. FIG. 10 is a schematic longitudinal sectional view showing the N-MOS circuit element.

According to FIG. 10, a P-MOS 450 is constituted
5 in an N-type well region 402 by using a general MOS
process to plant ions or introduce and diffuse other
impurities in a P-conductor Si substrate 401, and an N-
MOS 451 is constituted in a P-type well area 403. The
P-MOS 450 and N-MOS 451 are each constituted of a gate
10 wiring 415 formed by polysilicon deposited in a
thickness of 4000 to 5000 μm in a CVD process, and a
source region 405, drain region 406, and the like with
N-type or P-type impurities introduced therein via a
gate insulating film 408 with a thickness of several
15 hundreds of micrometers. A C-MOS logic is constituted
by the P-MOS 450 and N-MOS 451.

An N-MOS transistor 301 for driving the element is
constituted of a drain region 411, source region 412
and gate wiring 413 in the P-type well substrate 402 by
20 the impurities introducing and diffusing steps.

Here, when the N-MOS transistor 301 is used as an
element driver, a distance L between drain and gate
constituting one transistor is about 10 μm at minimum.
The value of 10 μm includes widths of source and drain
25 contacts 417. The width is $2 \times 2 \mu\text{m}$, but actually the
half also serves as the adjacent transistor, and the
width is therefore the half, that is, 2 μm . The value

also includes a distance between the contact 417 and the gate 413, that is $2 \times 2 \mu\text{m} = 4 \mu\text{m}$, and a width of the gate 413, that is, $4 \mu\text{m}$. Therefore, the total distance L is $10 \mu\text{m}$.

5 An oxide film separating region 453 with a thickness of 5000 to 10000 μm is formed between the elements by field oxidation, and the elements are separated from each other. This field oxide film acts as a first layer of regenerator layer 414.

10 After the respective elements are formed, an interlayer insulating film 416 is deposited as PSG, BPSG films, and the like in a thickness of about 7000 μm by the CVD process. The film is subjected to a heat treatment, that is, a flatting treatment, and the like,
15 and wired via a contact hole by an AI electrode 417 as a first wiring layer. Thereafter, an interlayer insulating film 418 of an SiO_2 film is deposited in a thickness of 10000 to 15000 μm by the plasma CVD process, and further a through hole is formed.

20 The N-MOS circuit is formed before the floating element is formed. Subsequently, the circuit is connected to the oscillation circuit as the energy converting means of the present invention via the through hole.

25 In the example shown in FIG. 6, the electromagnetic induction by the coil is utilized in the outside energy for supplying the power to start the

element 11, but additionally light brightness/darkness may be utilized. To convert the light brightness/darkness to the electric signal, a material whose resistance value changes with light irradiation (e.g. photoconductor) can be used to generate the power by a photoconductive effect. Examples of the photoconductor include two-dimensional/three-dimensional alloys such as CdS, InSb and $\text{Hg}_{0.8}\text{Cd}_{0.2}\text{Te}$, and GaAs, Si, Va-Si, and the like. When heat is used as the electromotive force, the power can be generated from a material radiation energy by quantum effect. (Second Embodiment)

FIG. 11 is a block diagram showing the inner constitution of the solid semiconductor element according to a second embodiment of the present invention, and the exchange of the element with the outside. A solid semiconductor element (hereinafter referred to simply as the "element") 21 shown in FIG. 11 is disposed in the ink tank, and includes energy converting means 24 for converting an electromotive force 22 supplied to the element 21 from the outside A to a power 23, information acquiring means 25 started by the power converted by the energy converting means 24, discrimination means 26, information storing means 27, information communicating means 28, and receiving means 29. The second embodiment is different from the first embodiment in that the element has a receiving

function, that is, the receiving means 29, and similar to the first embodiment in other respects. The electromagnetic induction, heat, light, ray, and the like can be applied to the electromotive force 22

5 supplied to operate the element 21. Moreover, at least the energy converting means 24, information acquiring means 25 and receiving means 29 are preferably formed on the surface of the element 21 or in the vicinity of the surface.

10 The information acquiring means 25 acquires the ink information in the ink tank as the environmental information of the element 21. The receiving means 29 receives an input signal 30 from the outside A or B. The discrimination means 26 allows the information
15 acquiring means 25 to acquire the ink information in response to an input signal from the receiving means 29, compares the acquired ink information with the information stored in the information storing means 27, and judges whether or not the acquired ink information
20 satisfies the predetermined condition. The information storing means 27 stores various conditions for comparison with the obtained ink information and ink information itself obtained from the information
25 acquiring means 25 as the data table. The information communicating means 28 converts the power to the energy for transmitting the ink information to the outside A, B or C, and displays and transmits a discrimination

result obtained by the discrimination means 26 to the outside A, B or C in response to a command from the discrimination means 26.

FIG. 12 is a flowchart showing the operation of the element shown in FIG. 11. Referring to FIGS. 11 and 12, when the electromotive force 22 is applied to the element 21 from the outside A, the energy converting means 24 converts the electromotive force 22 to the power 23, and the information acquiring means 25, discrimination means 26, information storing means 27, information communicating means 28 and receiving means 29 are started by the power.

In this state, the outside A or B transmits the signal 30 to the element 21 to ask for the ink tank inside information. The input signal 30 is a signal for asking the element 21, for example, whether or not the ink still remains in the ink tank, and received by the receiving means 29 (step S21 of FIG. 12). Then, the discrimination means 26 allows the information acquiring means 25 to acquire the ink information in the ink tank such as the ink residual amount, ink type, temperature, and pH (step S22 of FIG. 12), reads the condition for referring to the acquired ink information from the information storing means 27 (step S23 of FIG. 12), and judges whether the acquired ink information satisfies a set condition (step S24 of FIG. 12).

In the step S24, when it is judged that the

acquired information does not satisfy the set condition, or when it is judged that the acquired information satisfies the set condition, this is transmitted to the outside A, B or C (steps S25, S26).

5 In this case, the acquired information may be transmitted together with the judgment result. The information is transmitted when the information communicating means 28 converts the power obtained by energy conversion to the energy for transmitting the
10 ink information in the ink tank to the outside. The magnetic field, light, shape, color, radio wave, sound, and the like can be used as the transmitting energy, and the energy is changed in accordance with the judgment result. In accordance with a question content
15 to be judged (for example, whether the ink residual amount is 2 ml or less, or the ink pH changes), the transmission method may be changed.

Additionally, the electromotive force may also transmitted to the element 21 together with the input
20 signal 30 from the outside A or B. For example, when the electromotive force is electromagnetic induction, the signal for asking the ink residual amount is transmitted. When the electromotive force is light, the signal for asking pH is transmitted. The signal
25 may be transmitted in accordance with information type in this manner.

According to the second embodiment, the element has

a function of receiving the signal from the outside.
Therefore, in addition to the effect of the first
embodiment, questions transmitted from the outside via
various types of signals can be answered, and the
5 element can exchange the information with the outside.

(Third Embodiment)

FIG. 13 is a block diagram showing the inner
constitution of the solid semiconductor element
according to a third embodiment of the present
10 invention and the exchange with the outside. A solid
semiconductor element (hereinafter referred to simply
as the "element") 31 shown in FIG. 13 is disposed in
the ink tank, and includes energy converting means 34
for converting an electromotive force 32 supplied to
15 the element 31 from the outside A to a power 33, and
buoyancy generating means 35 for using the power
converted by the energy converting means 34 to generate
buoyancy.

In the third embodiment, when the electromotive
20 force 32 is applied to the element 31 from the outside
A, the energy converting means 34 converts the
electromotive force 32 to the power 33, the buoyancy
generating means 35 uses the power 33 to generate the
buoyancy of the element 31, and the element 31 is
25 floated on the ink surface. By the buoyancy, the
element 31 may be positioned not only on the ink
surface but also at a constant distance below the ink

surface in order to prevent the ink from being ejected in an empty state.

FIGS. 14A and 14B shows a position of the element floated in the ink of the ink tank together with the ink consumption change. Additionally, since the ink tank shown in FIGS. 14A and 14B is similar in constitution to the ink tank shown in FIG. 6, description thereof is omitted.

10 In the ink tank shown in FIGS. 14A and 14B, when the ink of a negative pressure generating member 37 is discharged to the outside via an ink supply port 36, the consumed amount of ink is introduced to the negative pressure generating member 37 from the ink chamber. Thereby, the element 1 in the ink 38 in the
15 ink chamber exists at a given distance from an ink surface H, and moves as the position of the ink surface is lowered with the ink consumption.

FIG. 15 is a flowchart for checking the position of the element 31, and discriminating a need for tank replacement. Referring to steps S31 to S34 of FIGS. 13 and 15, the outside A or B (e.g., the ink jet recording apparatus) transmits light to the element 31. When the outside A or B (e.g., the ink jet recording apparatus) or C receives the light, the position of the element 31
25 is detected. The ink jet recording apparatus judges, in accordance with the detected position of the element 31, whether or not it is necessary to replace the ink

tank. If necessary, the tank replacement is notified via sound, light, or the like.

Examples of a method of detecting the position of the element 31 include a method of using the
5 oscillation circuit 102 shown in FIG. 5 as the energy converting means 34, disposing the circuit and outside resonance circuit 101 outside the ink tank, and detecting the position based on the output from the oscillation circuit 102 similarly as the first
10 embodiment. Moreover, the examples include: a method of disposing light emitting means opposite to light receiving means in a position in which the element 31 passes with displacement of the ink surface, shielding the light emitted from the light emitting means by the element 31, and detecting the position of the element
15 31; a method of reflecting the light emitted from the light emitting means by the element 31, and detecting the position of the element 31 by the reflected light; and the like.

20 According to the third embodiment, the element 31 can be floated without disposing the hollow portion in the element described in the first embodiment with reference to FIGS. 9A to 9G. Additionally, even when the buoyancy or the like necessary for the element 31
25 changes by a change of liquid specific weight or another environment for using the element 31, the energy converting means 34 converts the electromotive

force 32 from the outside, and the element can constantly be set and disposed in a desired position. Therefore, the element 31 can be used irrespective of the environment where the element 31 is disposed.

5 Additionally, the third embodiment can also appropriately be combined with the aforementioned first and second embodiments.

(Fourth Embodiment)

10 In a fourth embodiment, a function of transmitting the information to another element is imparted to the element having the constitution similar to that of the first or second embodiment, and a plurality of elements are disposed in the object.

15 First, a concept of the fourth embodiment will be described with reference to FIGS. 16A to 16C. FIGS. 16A to 16C are explanatory views showing the concept of the fourth embodiment of the present invention.

20 In an example shown in FIG. 16A, a plurality of elements 41, 42, ... 43 constituted similarly as the first embodiment are disposed in the object. When an electromotive force P is supplied to the respective elements 41, 42, ... 43 from the outside A or B, the respective elements 41, 42, ... 43 obtain the environmental information. Subsequently, acquired
25 information a of the element 41 is transmitted to the element 42, and the acquired information a, b of the elements 41, 42 are successively transmitted to the

next element. The last element 43 transmits all the acquired information to the outside A or B.

Moreover, in an example shown in FIG. 16B, a plurality of elements 51, 52, ... 53 constituted similarly as the second embodiment are disposed in the object. The electromotive force P is supplied to the respective elements 51, 52, ... 53 from the outside A, B or C. For example, when a predetermined question is inputted to the element 53 from the outside A or B via the signal, the element 51 or 52 acquires the corresponding information and answers the question. The question/reply of the element 51 or 52 is successively transmitted to another element, and the desired element 53 answers the question to the outside A, B or C.

Furthermore, in an example shown in FIG. 16C, a plurality of elements 61, 62, ... 63 constituted similarly as the second embodiment are disposed in the object. The electromotive force P is supplied to the respective elements 61, 62, ... 63 from the outside A, B or C. For example, when a certain signal is inputted to the element 63 from the outside A or B, the signal is successively transmitted to the elements 62 and 61. The element 61 displays the signal to the outside A, B or C.

Additionally, in the examples of FIGS. 16A to 16C, one of the plurality of elements may be provided with

the buoyancy generating means similarly as the third embodiment.

The concept of the fourth embodiment has been described above. The detection of the ink information based on the aforementioned concept according to the fourth embodiment will be described hereinafter with reference to FIGS. 17 and 18. In FIGS. 17 and 18, W denotes a printing scanning direction, and P denotes the electromotive force.

FIG. 17 shows an example in which the element constituted by appropriately combining the first, second and third embodiments is disposed in the ink tank and an ink jet recording head connected to the tank. In this example, an element 71 is constituted by adding the buoyancy generating means of the third embodiment and function of transmitting the information to another element 79 to the first embodiment, and disposed in a desired position in an ink 73 in an ink tank 72. On the other hand, the element 79 constituted similarly as the second embodiment and having an ID function (identification function) is disposed in a recording head 78 for ejecting, via an ejection port 77, a printing ink supplied via a liquid path 75 and liquid chamber 76 connected to the ink tank 72 via an ink supply port 74. The power may be supplied to the element 79 by bringing an electrode portion disposed on the element surface in contact with a contact portion

on an electric substrate for driving the recording head 78.

Subsequently, when the electromotive force is supplied to the respective elements 71, 79 from the outside, the element 71 in the ink 73 acquires the ink information such as ink residual amount information, and the element 79 on a recording head 78 side transmits the ID information for judging the ink residual amount for tank replacement to the element 71. Then, the element 71 compares the acquired ink residual amount with ID, and instructs the element 79 to inform the outside of the tank replacement only when these meet with each other. The element 79 receives this, and transmits a signal indicating the tank replacement to the outside or outputs sound, light, and the like to human eyes and sense of hearing.

When a plurality of elements are disposed in the certain object, a complicated information condition can be set.

Moreover, in the example shown in FIGS. 16 and 17, the electromotive force is supplied to the respective elements, but this constitution is not limited, and the electromotive force supplied to the certain element may successively be transmitted to another element together with the information.

For example, as shown in FIG. 18, an element 81 is constituted by adding the buoyancy generating means

similar to that of the third embodiment and functions of transmitting the information and supplying the electromotive force to another element to the constitution of the first embodiment. An element 82 is
5 constituted by adding the buoyancy generating means similar to that of the third embodiment and function of transmitting the information and supplying the electromotive force to another element to the constitution of the second embodiment. These elements
10 are disposed in the desired positions in the ink 73 in the ink tank 72 similarly as in FIG. 17. On the other hand, an element 83 constituted similarly as the second embodiment and having the ID function (identification function) is disposed in the recording head 78
15 connected to the ink tank 72. The power may be supplied to the element 83 by bringing the electrode portion disposed on the element surface in contact with the contact portion on the electric substrate for driving the recording head 78.

20 Subsequently, when the electromotive force is supplied to the element 81 from the outside, one element 81 in the ink 73 acquires the ink information such as the ink residual amount information, and compares the information with an internal defined
25 condition. The element transmits the acquired ink residual amount information to the other element 82 together with the electromotive force for operating the

element 82, when the information needs to be transmitted to the other element 82. The other element 82 with the electromotive force supplied thereto receives the ink residual amount information

5 transmitted from the element 81, acquires the ink information such as ink pH information, and transmits the electromotive force for operating the element 83 to the element 83 on the recording head 78 side. Then, the recording head 78 side element 83 with the

10 electromotive force supplied thereto transmits the ID information for judging the ink residual amount or the ink pH for the tank replacement to the element 82. Subsequently, the element 82 compares the acquired ink residual amount information and pH information with the

15 ID information, and instructs the element 83 to inform the outside of the tank replacement only when these information meet with each other. The element 83 receives this, and transmits the signal for informing the outside of the tank replacement or outputs the

20 sound, light, and the like to human eyes and sense of hearing. A method of supplying the electromotive force together with the information to the other element from the certain element in this manner is also considered.

Additionally, for the recording head 78, the ink

25 is bubbled by heat of electricity/heat converting elements such as a heater in the liquid path, and the ink is supposedly ejected via a micro opening connected

to the liquid path by a bubble growth energy.

Other embodiments to which the aforementioned respective embodiments can be applied will be described hereinafter.

5 <Information Input Means>

In addition to the information about the ink and information acquiring means described above in the respective embodiments, examples of the information acquiring means for acquiring the information include:

- 10 (1) a sensor (ion sensor) for detecting ink pH, in which the SiO_2 film or the SiN film is formed as an ion sensitive film; (2) a pressure sensor having a diaphragm structure for detecting a pressure change in the tank; (3) a sensor for detecting the existing
15 position of a photodiode, and the ink residual amount, in which the photodiode for converting light to the heat energy and producing a pyroelectric effect; (4) a sensor for using a conductive effect of the material to
20 detect the presence/absence of the ink in accordance with a moisture amount in the tank; and the like.

A case in which the ion sensor is used as the information acquiring means will be described hereinafter in detail.

FIG. 19 is a sectional view of the ion sensor
25 disposed in the solid semiconductor element of the present invention. In FIG. 19, S denotes a source, B denotes a bias, and D denotes a drain.

As shown in FIG. 19, an ion sensitive film 302 formed of SiN or SiO₂ is formed on the surface of a spherical silicon 301 as a base of the solid semiconductor element, and a part of the film is disposed at an interval from the spherical silicon 301 via a gap 307. A gate insulating film 303 is formed on the surface of the ion sensitive film 302. Furthermore, an N-type well layer constituted of a source region 304a with N-type impurities introduced therein and N-type well layer formed of a drain region 304b are formed on the surface of the gate insulating film 303, and further a P-type well layer 305 is formed on the layers. Moreover, a reference electrode 306 is formed on a part of the surface of the spherical silicon 301 in a region in which the gap 307 is formed. This constitutes an ion sensor 300 as an ion selective field effect transistor (FET).

The gap 307 can be formed by forming a sacrifice layer to cover the reference electrode 306 before forming the ion sensitive film 302, and the like on the surface of the spherical silicon 301 with the reference electrode 306 formed thereon, subsequently forming the P-type well region 305, and subsequently etching/removing the sacrifice layer. Moreover, the gap 307 is connected to the outside of the ion sensor 300 via a connection portion (not shown). While the solid semiconductor element is disposed in the ink, the

ink can freely move in the gap 307 via the connection portion.

When the ion sensitive film 302 contacts the ink, an interface state potential is generated between the ion sensitive film 302 and the ink in accordance with the ion type and concentration in the ink. When a predetermined bias voltage is applied between source and drain of the ion sensor 300, a drain current flows in accordance with the interface state potential.

During measurement, an appropriate bias is applied between the reference electrode 306 and the source, and an output (drain current) corresponding to a sum of the interface state potential and bias is observed.

Alternatively, the ion sensor 300 is constituted as a source follower circuit, and the output may be obtained as the potential via a resistance.

Additionally, the ink for use in the ink jet recording apparatus is generally formed by solving or dispersing dye or pigment in water as a solvent.

Examples of the ink include a dye ion having a carboxyl group or a hydroxide group, a pigment set to be hydrophilic by a dispersant having the group, and pigment particles to which the groups are attached and which are dissolved or dispersed in water. As shown in FIGS. 20A and 20B, the dye or the pigment forms an associated state (a state of assembly) by a hydrogen bond or another relatively weak bond in the ink as an

aqueous solution. When the associated state occurs among several tens/hundreds of molecules, a polymeric color material molecule is virtually formed, an ink dynamic viscosity is lowered, and as a result the ejection property of the recording head is deteriorated. In FIGS. 20A and 20B, DM denotes a dye molecule.

When the aforementioned associated state is formed, an activity of the carboxyl group or the hydroxide group as the ion is apparently lowered, and an effective molecular weight of the ion itself increases. Therefore, the detected potential in the ion sensor 300 is changed. The solid semiconductor element of the present example is disposed, for example, in contact with the recording head ink, the associated state of the dye ion in the ink is detected by the ion sensor 300, a recovering operation of the recording head is performed if necessary, and the ink in the recording head is brought to a constant dissociated state.

FIG. 21A is a diagram showing one example of a circuit for outputting a detection result in the ion sensor, and FIG. 21B shows the circuit of FIG. 21A as a logic circuit. Here, the oscillation circuit whose oscillation frequency changes in accordance with the ion concentration will be described.

In an example of FIGS. 21A and 21B, MOS

transistors 320, 321 are connected in series with each other to constitute inverter circuits 322, 323. These inverter circuits 322, 323 are connected in a two-stages annular shape to constitute the oscillation circuit. Furthermore, the output of the inverter circuit 323 is extracted as the oscillation output via the first-stage inverter circuit 322 as a buffer. The ion sensor 300 is inserted between the output of the inverter circuit 322 (i.e., the input of the inverter circuit 323) and a ground point. According to the circuit, the oscillation frequency changes in accordance with the detected potential in the ion sensor 300. Therefore, when the oscillation frequency is detected, the ink ion concentration can be detected.

When the solid semiconductor element of the present invention is disposed in the ink of the ink tank, particularly in the vicinity of the liquid surface, as described above, the color material molecules in the ink are associated, the polymer state is virtually formed, and the molecules settle in the vicinity of the bottom surface. Generation of a concentration distribution and pH distribution in the ink in the ink tank can be detected. When the result is transmitted to the outside, an operation for removing these distributions can be performed.

A detected voltage value in the ion sensor 300 is governed by Nernst equation, and is therefore a

function of temperature. To eliminate an influence of temperature, for example, the temperature sensor is also separately disposed, so that a measured value of ion concentration can be corrected in accordance with the measured value of temperature. When the temperature sensor is disposed in this manner, the ion sensor and temperature sensor may be formed in the same element, or may be formed in separate elements. With the separate elements, as in the fourth embodiment, the information acquired by the element with the temperature sensor formed therein may be transmitted to the element with the ion sensor formed therein.

Moreover, according to Stokes' law derived from hydrodynamics, an ion molar concentration λ is represented by the following equation:

$$\lambda = \frac{|Z| \cdot F^2}{6\pi N \eta r} \quad (14)$$

(here, Z: ion charge number, F: Faraday constant, N: molecule number per unit area, η : viscosity, r: ion radius). Moreover, an ion diffusion coefficient D is represented by the following equation:

$$D = \frac{RT\lambda}{|Z| \cdot F^2} \quad (15)$$

(here, R: gas constant, T: absolute temperature). It is assumed that this Stokes' law of hydrodynamics can be applied to ion movement in the ink. In this case, an ink molar conductivity λ and diffusion coefficient D are measured and stored in the information storing means disposed in the element or a memory disposed beforehand outside the element, before the ink is injected to an ink cartridge or the ink tank.

When only the color material component (dye or pigment) in the ink is noted, the ion radius r , viscosity η , and charge number Z are variable parameters.

Furthermore, a dipole moment μ of the noted ion is represented by the following equation.

$$\mu = \frac{\lambda}{F} \quad (16)$$

15

An ink dielectric constant ϵ is represented by the following equation:

$$\epsilon = 2\pi N \frac{\mu^2 g}{kT} \quad (17)$$

(here, g : amount determined by relative orientation of adjacent molecules, k : Boltzmann constant).

The aforementioned ion sensor is used. The detected potential change is considered to be proportional to (ion charge number Z /ion radius r). A

change of viscosity η can relatively be estimated from the equation (10). It is considered that a pulse control for setting the ejection property to be constant in accordance with the change of the viscosity η can be remarkably effective means.

<Constitution of Ink Tank>

Some constitution examples of the ink tank to which the solid semiconductor element of the aforementioned embodiments can be applied are shown in FIG. 22 to FIG. 25.

In an ink tank 501 shown in FIG. 22, a flexible ink bag 502 with the ink contained therein is disposed in a housing 503, a bag inlet 502a is closed by a rubber stopper 504 fixed to the housing 503, a hollow needle 505 for deriving the ink is stuck through the bag via the rubber stopper 504, and the ink is supplied to an ink jet head (not shown). A solid semiconductor element 506 of the present invention is disposed in the ink bag 502 of the ink tank 501, and the information of the ink contained in the ink bag 502 can be detected.

Moreover, in an ink tank 511 shown in FIG. 23, an ink jet head 515 for ejecting the recording ink to a recording sheet S is attached to an ink supply port 514 of a housing 512 in which an ink 513 is contained. A solid semiconductor element 516 of the present invention is disposed in the ink 513 in the ink tank 511, and the information of the ink 513 in the housing

512 can be detected.

Moreover, an ink tank 521 shown in FIG. 24 has a constitution similar to that of the ink tank shown in FIG. 6, and the like, and includes: an ink chamber in which an ink 522 is contained and which is substantially in a sealed state excluding a communication path 524; a negative pressure generating chamber in which a negative pressure generating member 523 is contained and which is in an atmosphere connected state; and the communication path 524 for connecting the ink chamber to the negative pressure generating chamber in a lowermost portion of the tank. In the ink tank 521 constituted as described above, solid semiconductor elements 525, 526 of the present invention are disposed in the ink chamber and negative pressure generating chamber, respectively, so that the information about the ink of each divided chamber may be exchanged.

Moreover, for an ink tank 531 shown in FIG. 25, a porous member 532 for absorbing/holding the ink is contained inside, and an ink jet head 533 in which the contained ink is used for a recording purpose is attached. Even in the tank 531 constituted in this manner, similarly as the constitution shown in FIG. 17, 18, solid semiconductor elements 534, 535 of the present invention are disposed on an ink tank 531 side and ink jet head 533 side, respectively, and the

information about the ink in the respective divided constitutional portions may be exchanged.

<Ink Jet Recording Apparatus>

FIG. 26 is a schematic perspective view showing the ink jet recording apparatus on which the ink tank provided with the solid semiconductor element of the present invention is mounted. A head cartridge 601 mounted on an ink jet recording apparatus 600 shown in FIG. 26 has a liquid ejection head for ejecting the printing/recording ink, and an ink tank for holding the liquid supplied to the liquid ejection head as shown in FIG. 22 to FIG. 25. Moreover, outside energy supply means 622 for supplying the electromotive force as an outside energy to the solid semiconductor element (not shown) disposed in the ink tank, and means (not shown) for bidirectionally communicating the information with the solid semiconductor element are disposed in the recording apparatus 600.

As shown in FIG. 26, the head cartridge 601 is mounted on a carriage 607 engaged with a spiral groove 606 of a lead screw 605 rotated with forward/reverse rotation of a drive motor 602 and via drive force transmission gears 603 and 604. The head cartridge 601 reciprocates/moves with the carriage 607 along a guide 608 by the drive power of the drive motor 602 in directions of arrows a and b. The ink jet recording apparatus 600 is provided with recording material

conveying means (not shown) for conveying a printing sheet P as a recording material which receives the ink or another liquid ejected from the head cartridge 601. By the recording material conveying means, a sheet
5 press plate 610 of the printing sheet P conveyed on a platen 609 presses the printing sheet P onto the platen 609 in the movement direction of the carriage 607.

Photocouplers 611 and 612 are disposed in the vicinity of one end of the lead screw 605. The
10 photocouplers 611 and 612 are home position detection means for checking presence of a lever 607a of the carriage 607 in regions of the photocouplers 611 and 612 and changing a rotation direction of the drive motor 602. A support member 613 for supporting a cap
15 member 614 to cover a front surface including an ejection port of the head cartridge 601 is disposed in the vicinity of one end of the platen 609. Moreover, ink suction means 615 is disposed to suck the ink accumulated in the cap member 614 by empty ejection
20 from the head cartridge 601. The head cartridge 601 is sucked/recovered by this ink suction means 615 via an opening of the cap member 614.

A main body support 619 is disposed in the ink jet recording apparatus 600. A moving member 618 is
25 supported by the main body support 619 to be movable in a back to forth direction, that is, in a direction crossing at right angles to the movement direction of

the carriage 607. A cleaning blade 617 is attached to the moving member 618. The cleaning blade 617 is not limited to this mode, and another known cleaning blade may be used. Furthermore, a lever 620 for starting suction during the suction/recovery operation by the ink suction means 615 is disposed. The lever 620 moves with movement of a cam 621 which meshes with the carriage 607, and is moved/controlled by known transmission means for transmitting the drive force from the drive motor 602 by changing a clutch. An ink jet recording controller for transmitting a signal to a heat generator disposed in the head cartridge 601 and driving/controlling the aforementioned respective mechanisms is disposed on a recording apparatus main body side, and is not shown in FIG. 24.

In the ink jet recording apparatus 600 having the aforementioned constitution, the head cartridge 601 reciprocates/moves over a whole width of the printing sheet P with respect to the printing sheet P conveyed on the platen 609 by the recording material conveying means. During the movement, when the drive signal supply means (not shown) supplies the drive signal to the head cartridge 601, the ink (recording liquid) is ejected to the recording material from the liquid ejection head portion and the sheet is recorded.

Additionally, in FIG. 26 an outer covering of the ink jet recording apparatus is not shown, but a

translucent covering may be used such that an inside state can be seen. When a translucent ink tank is used together, and light is used as transmission means, a user can see tank light. For example, it can easily be seen that "the tank needs to be replaced", and the user can be reminded of the need for tank replacement. In a conventional art, the light emitting means is disposed in an operation button of the recording apparatus main body. When the light emitting means emits light, the user is notified of the tank replacement. However, the light emitting means frequently performs several display functions. Therefore, even when the light emitting means emits the light, the user cannot easily understand a meaning of emitted light in many cases.

15 <stabilization of Floating Type Solid Semiconductor Element on Liquid Surface>

When the solid semiconductor element has a hollow portion as shown in FIGS. 9A to 9G, and the power is supplied to the solid semiconductor element by the oscillation circuit and outside resonance circuit shown in FIG. 5, even in any state of the ink tank, a stable magnetic flux (magnetic field) needs to act between the oscillation circuit and outside resonance circuit formed in the element. That is, the direction of the element with respect to the outside resonance circuit needs to be stabilized. However, when the element floats in the ink or another liquid, the liquid surface

vibrates by outside vibration, and element direction sometimes fluctuates. Even in this case, the gravity center of the floating type solid semiconductor element is determined as follows, so that the element holds its stable posture in the liquid.

As shown in FIGS. 27A and 27B, when a solid semiconductor element 210 formed as a sphere is floated in the liquid, to obtain a balanced state as shown in FIG. 27A, the following relations need to be established:

- (1) a buoyancy F = material weight W ; and
 - (2) a buoyancy action line meets with a weight action line (line passed through the gravity center).
- In FIGS. 27A and 27B, L denotes an ink surface, and MC denotes a metacenter.

Here, an intersection of the weight action line in the balanced state (dashed line in FIG. 27B) with the buoyancy action line during tilting (solid line in FIG. 27B) is the metacenter, and a distance h between the metacenter and the gravity center G is a height of the metacenter.

The metacenter of the solid semiconductor element 210 is positioned higher than the gravity center G , and a couple of forces (restoring force) acts in a direction to return the original balanced position. A restoring force T is represented by the following equation.

$$T = Wh\sin\theta = Fh\sin\theta = \rho g V h \sin\theta \quad (>0) \quad (18)$$

Here, V denotes a volume of the liquid discharged by the solid semiconductor element 210, and ρg is a specific weight of the solid semiconductor element 210.

5 In order to set the restoring force T to be positive, $h > 0$ is a necessary and sufficient condition.

Then, the following equation results from FIG. 27B.

$$h = (I/V) - \overline{CG} \quad (19)$$

10

Here, I denotes an inertia moment around an O axis. Therefore, the following relation is a necessary condition, such that the solid semiconductor element 210 steadily floats in the ink, supplies the induced
15 electromotive force from the outside resonance circuit and bidirectionally communicates with communication means outside the element.

$$(I/V) > \overline{CG} \quad (20)$$

<Pressure Sensor>

20

Here, one example of the pressure sensor described in the first embodiment and utilized for detecting the liquid density will be described in detail.

The pressure detecting sensor shown in FIG. 28 is a semiconductor strain gauge in which a piezo resistance effect in the polysilicon film is utilized. The sensor is formed in a constantly ink contacting position of the surface of the solid semiconductor element formed of the spherical silicon. A polysilicon resistance layer 221 is formed as a partially raised diaphragm via a hollow portion 225 on the surface of a spherical silicon 200. A wiring 222 formed of Cu or W is disposed in opposite ends of the raised region of the polysilicon resistance layer 221. Moreover, the polysilicon resistance layer 221 and wiring 222 are coated with a protective film 223 formed of SiN, and constitute pressure adjustment means.

A pressure detection principle by the pressure detecting sensor shown in FIG. 28 will next be described with reference to FIGS. 28 and 29. FIG. 29 is a circuit diagram of a circuit for monitoring an output from the polysilicon resistance layer shown in FIG. 28.

In FIG. 29, it is assumed that a normal resistance value of the polysilicon resistance layer 221 is r . Then, the following current flows through an ammeter 230.

$$i = VDD / \{R_0 + R \times r(R + r)\} \quad (21)$$

Moreover, polysilicon has a property such that the resistance value increases in proportion to

displacement. Therefore, when the polysilicon resistance layer 221 is displaced by the pressure change of a channel 212, the resistance value r of the polysilicon resistance layer 221 changes, and as a result a current i measured by the ammeter 230 also changes. That is, the displacement amount of the polysilicon resistance layer 221 is known from the change of the current i , and the ink pressure can thereby be detected.

10 This respect will be described in further detail. When a length of the polysilicon resistance layer 221 is L , and a sectional area is S , resistivity ρ is used to represent a total resistance value R as follows.

$$R = \rho L / S \quad (22)$$

15 Here, when the polysilicon resistance layer 221 changes with the pressure change, a length is long, that is, $L + \Delta L$, and the resistance value increases. On the other hand, the sectional area is small, that is, $S - \Delta S$. Moreover, ρ changes to ρ' . A relation between an increase ΔR of the resistance value and an increase ΔL of the length is represented as follows.

$$\begin{aligned} R + \Delta R &= \frac{\rho' (L + \Delta L)}{S - \Delta S} \\ &\approx \frac{\rho L}{S} + \Delta L \frac{\rho'}{S - \Delta S} \quad (23) \end{aligned}$$

Furthermore, the following equation results.

$$\begin{aligned}\frac{\Delta R}{R} &= \frac{\rho'}{\rho} \times \frac{S}{S - \Delta S} \times \frac{\Delta L}{L} \\ &= kg \times \frac{\Delta L}{L} \quad (24)\end{aligned}$$

Here, kg denotes a change coefficient of the resistance value with respect to the strain.

Moreover, when a bridge circuit or the like is used to detect a change ΔR of the resistance value, the pressure fluctuation can be obtained.

Polysilicon has a property such that strain pressure changes with temperature. Therefore, the pressure detecting sensor including the polysilicon resistance layer 221 preferably further comprises a temperature sensor for monitoring the temperature of the polysilicon resistance layer 221. That is, when a voltage VDD is supplied to the polysilicon resistance layer 221 via the temperature sensor, the resistance change of the polysilicon resistance layer 221 by an environmental temperature change is compensated, and the ink pressure can be detected more accurately.

<Application of Solid Semiconductor Element to Apparatus other than Ink Tank>

The present invention has been described above by way of an example in which the ink information of the ink tank for use in the ink jet recording apparatus is detected. The present invention is not limited to

this, and effective in detecting the information about the liquid contacting the element from the outside.

Here, an example will be described in which the solid semiconductor element of the present invention is applied to an apparatus other than the ink tank.

FIG. 30 is a sectional view of a water tube in which the solid semiconductor element of the present invention is disposed. In the example shown in FIG. 30, a solid semiconductor element 153 of the present invention is fixed in a water tube 151 through which the liquid flows in a shown arrow direction. The solid semiconductor element 153 has the oscillation circuit (not shown) as the energy converting means, and the outside resonance circuit 152 for supplying the power to the solid semiconductor element 153 via the resonance circuit is disposed in the vicinity of the solid semiconductor element 153 outside the water tube 151. When the solid semiconductor element 153 is disposed in the water tube 151, the resonance frequency range by the outside resonance circuit 152 is varied, and a liquid property change can be read along the liquid flow in the water tube 151 from the output generated from the oscillation circuit in the solid semiconductor element 153.

FIG. 31 is a schematic sectional view of a micro valve in which the solid semiconductor element of the present invention is disposed. As shown in FIG. 31, in

a micro valve 160, a piezoelectric element 162 is attached to a wall surface. The valve includes: a liquid chamber 161 with a inflow port and outflow port of the liquid formed therein; inflow valves 164a, 164b which are disposed in the inflow port of the liquid chamber 161 and which open only inwardly in the liquid chamber 161; and outflow valves 166a, 166b which are disposed in the outflow port of the liquid chamber 161 and which open only outwardly from the liquid chamber 161. The inflow port is connected to an inflow tube 163, and the outflow port is connected to an outflow tube 165. Moreover, a solid semiconductor element 167 of the present invention is fixed in the liquid chamber 161.

In the micro valve 160 shown in FIG. 31, deflection/deformation of the piezoelectric element 162 caused by applying the voltage to the piezoelectric element 162 is utilized to change a volume of the liquid chamber 161 as shown in FIGS. 32A and 32B. That is, when the piezoelectric element 162 is deformed as shown in FIG. 32A, the volume of the liquid chamber 161 increases, the inflow valves 164a, 164b then open, and the liquid flows into the liquid chamber 161 via the inflow tube 163. Thereafter, when the piezoelectric element 162 is deformed as shown in FIG. 32B, the volume of the liquid chamber 161 decreases, the outflow valves 166a, 166b then open, and the liquid flows to

the outflow tube 165 out of the liquid chamber 161. When this operation is repeated, the liquid can be transmitted to the outflow tube 165 from the inflow tube 163 via the liquid chamber 161.

5 The solid semiconductor element 167 disposed in the liquid chamber 161 can detect a chemical property change of the liquid in the liquid chamber 161 with time. The physical property is estimated from the detected chemical property change, and a driving
10 condition of the piezoelectric element 162 can be optimized. As a result, the micro valve 160 shown in FIG. 31 can also be applied to a quantitative pump, an ink jet head, and other devices for ejecting a constant amount of liquid droplets.

15 FIG. 33 is a schematic sectional view of an ink jet device to which the micro valve shown in FIG. 31 is applied. An ink jet device 170 shown in FIG. 33 comprises: a liquid chamber 171 to which a piezoelectric element 172 is attached; a supply tube
20 173 connected to an inflow port of the liquid chamber 171; and an ejecting portion 175 connected to an outflow port of the liquid chamber 171 and having an orifice 175a formed therein. Inflow valves 174a, 174b which open only inwardly in the liquid chamber 171 are
25 disposed in the inflow port of the liquid chamber 171, and outflow valves 176a, 176b which open only outwardly from the liquid chamber 171 are disposed in the outflow

port of the liquid chamber 171. A solid semiconductor element 177 is fixed in the liquid chamber 171.

5 A basic operation of the ink jet device 170 shown in FIG. 33 is similar to that of the micro valve 160 shown in FIGS. 32A and 32B. When the piezoelectric element 172 is driven, the liquid supplied via the supply tube 173 is ejected as a liquid droplet from the orifice 175a of the ejecting portion 175 via the liquid chamber 171. Even in the ink jet device 170, the driving of the piezoelectric element 172 is optimized based on the detection result of the solid semiconductor element 177, and a liquid droplet ejection property can be optimized.

10 As described above, the present invention is effective in obtaining the information about the liquid in any apparatus in which the liquid is handled. In a most preferable case, as described in the aforementioned embodiments, the present invention is applied to the apparatus for supplying the ink contained in the detachably attached ink tank to the ink jet recording head, detecting the ink information about an ink jet printer for printing the recording sheet with the ink droplet ejected from the recording head, transmitting the information to the ink jet printer, and controlling the printer in an optimum method, or maintaining the inside of the tank in an optimum state.

Moreover, in the aforementioned respective
embodiments, the example in which the solid
semiconductor element is disposed in the ink tank,
water tube, micro valve, or another apparatus for
5 handling the liquid has been described, but the
function of the solid semiconductor element may
directly be imparted to the apparatus.

As described above, according to the present
invention, since the function of acquiring the
10 information about the liquid (ink) and function of
transmitted the acquired information to the outside are
formed in the element itself, the acquiring of the
information about the liquid and transmitting of the
information to the outside can efficiently be
15 performed. Particularly, when the solid semiconductor
element of the present invention is applied to the ink
tank, the driving of the recording head is controlled
based on the information acquired by the solid
semiconductor element, and high-quality recording can
20 be performed. Concretely, even when the ink tank is
replaced with another ink tank, or a different type of
ink is inserted, this can be detected. Moreover, the
ink viscosity and surface tension changes are
estimated, the driving condition of the recording head
25 is optimized/controlled based on the estimation result,
and the stable ejection property can be kept.

A constitution in which the solid semiconductor

element is utilized in respective color ink tanks for achieving color recording will next be described.

(Fifth Embodiment)

FIG. 34 is a schematic constitution diagram showing the ink jet recording apparatus according to a fifth embodiment of the present invention. An ink jet recording apparatus 1600 shown in FIG. 34 is provided with a carriage 1607 on which a liquid ejection head (not shown) for ejecting the printing/recording ink droplet and respective color ink tanks 1500 for holding the liquid to be supplied to the liquid ejection head are mounted. As the respective color ink tanks 1500, four color tanks of black B, cyan C, magenta M, yellow Y are mounted.

Respective solid semiconductor elements 1011 having communication functions with different response conditions are disposed in the respective color ink tanks, and can communicate with a communication circuit 1150 of the ink jet recording apparatus 1600 disposed outside the ink tank 1500.

The communication circuit 1150 can communicate with communication means of the solid semiconductor element 1011 disposed in the ink tank 1500 by a resonance circuit 1102 constituted of a frequency modulator 1152 and induction coil 1151. The solid semiconductor element 1011 can communicate by resonance by electromagnetic induction of the resonance circuit

1102. In order to achieve the communication function, an induction coil L is wound around the surface of the solid semiconductor element 1011 as shown in FIG. 35.

Moreover, to change the response condition of the
5 element for each color, the winding number, length, and the like of the coil L on the solid semiconductor element for each color are changed particularly in the present example, so that the resonance frequency
10 differs in the solid semiconductor element 1011 with each color. The communication circuit 1150 can modulate the electromagnetic induction frequency by the frequency modulator 1152. The resonance frequency of the solid semiconductor element corresponding to the color for the communication is synchronized (tuned),
15 and independent communication for each color is enabled. For example, when the communication circuit 1150 is in synchronization with the resonance frequency for a cyan color, a synchronous signal is received only from the solid semiconductor element disposed in the
20 cyan-color ink tank, the circuit can communicate with the element only with respect to cyan-color tank inside information (when the synchronized signal is transmitted, only the element in the cyan color tank responds to the signal).

25 Moreover, the solid semiconductor element 1011 is provided with the induction coil L. Therefore, when the coil is used to assemble the oscillation circuit,

the electromagnetic induction by the resonance circuit 1102 of the communication circuit 1150 can be converted to the power. Therefore, the power for starting the circuit formed in the element can be supplied in the non-contact manner.

In the aforementioned ink jet recording apparatus, for example, the communication circuit 1150 transmits a signal with a frequency equal to the resonance frequency for the cyan color to the tank via an electromagnetic wave 1012 in order to exchange the information with the cyan-color tank. Then, the power is generated in the coil of the element in the cyan-color tank by the electromagnetic induction, and the circuit in the element can be started. Therefore, when means for acquiring the environmental information of the element or the means for transmitting the environmental information to the outside are disposed in the circuit in the element, the cyan-color tank inside information can be detected and notified to the outside.

FIG. 36 is a block diagram showing the inner constitution of the solid semiconductor element 1011 disposed for each color and the exchange with the outside.

The solid semiconductor element 1011 includes: receiving and energy converting means (oscillation circuit provided with the coil) 1014 for receiving a

signal of the electromagnetic wave 1012 transmitted from the communication circuit 1150 in the recording apparatus 1600 and converting the electromagnetic wave 1012 to a power 1013; and information acquiring means 5 1015, discrimination means 1016, information storing means 1017, and information transmission means 1018 started by the power obtained by the receiving and energy converting means 1014. The receiving and energy converting means 1014, information acquiring means 1015 10 and information transmission means 1018 are preferably formed on the surface of the element 1011 or in the vicinity of the surface.

The discrimination means 1016 receives the signal of the electromagnetic wave 1012 when the receiving and energy converting means (oscillation circuit provided 15 with the coil) 1014 resonates by the received electromagnetic wave 1012, and does not receive the signal when the means does not resonate. Subsequently, upon receiving of the signal of the electromagnetic wave 1012, the means allows the information acquiring means 1015 to acquire the ink tank inside information (e.g., the ink residual amount, ink color material 20 concentration, pH, temperature, and the like) as the environmental information of the element 1011. The discrimination means compares the acquired tank inside 25 information with the information stored in the information storing means 1017, and judges whether or

not it is necessary to transmit the acquired tank
inside information to the outside. The information
storing means 1017 stores various conditions for
comparison with the acquired tank inside information
5 and tank inside information acquired from the
information acquiring means 1015. Here, based on the
condition set beforehand in the information storing
means 1017, the discrimination means 1016 discriminates
the need for the tank replacement, for example, when
10 the ink residual amount is 2 ml or less or when the ink
pH largely changes.

The information transmission means 1018 converts
the power to the energy for transmitting the tank
inside information to the outside, and
15 displays/transmits the tank inside information to the
outside based on the command of the discrimination
means 1016. The magnetic field, light, shape, color,
radio wave, sound, and the like can be used as the
transmitting energy. For example, when it is judged
20 that the ink residual amount is 2 ml or less, a sound
is emitted to transmit the need for tank replacement to
the outside. Moreover, the transmission destination is
not limited to the communication circuit 1150 of the
ink jet recording apparatus, and particularly the
25 light, shape, color, sound, and the like may be
transmitted to the human senses of sight and hearing.
Furthermore, when it is judged that the raw ink

residual amount is 2 ml or less, the sound is emitted. When the ink pH largely changes, light is emitted. The transmission method may be changed in accordance with the information in this manner.

5 According to the fifth embodiment, the solid semiconductor element having the communication function of responding to the respective color ink tanks with different frequencies is disposed, and the element can individually exchange the information with the desired-
10 color tank.

 Moreover, the solid semiconductor element for each color converts the electromagnetic wave from the communication circuit disposed on the recording apparatus main body side to the power for starting the
15 discrimination means, information acquiring means, and information transmission means in the element. Therefore, the electric wiring does not have to be directly connected to the outside, and the element can be used in any position in the object, for example, in
20 the ink in which it is difficult to connect the electric wiring directly to the outside. When the element is disposed in the ink, the ink state can accurately be grasped in real time. Furthermore, it is unnecessary to dispose means (power source in the
25 present example) for storing the electromotive force for operating the element, and the element can therefore be miniaturized and used even in the narrow

place.

(Sixth Embodiment)

Another embodiment will next be described. The basic constitution of the solid semiconductor element is similar to the constitution shown in FIG. 36, but the response condition in the communication is different. Therefore, in the description, the same component as that of the fifth embodiment is denoted with the same reference numeral. In the sixth embodiment, different from the fifth embodiment, the frequency to be tuned for the communication is the same with respect to all the elements in the respective color ink tanks (the resonance frequency determined by the winding number, length, and the like of the coil L on the element is the same for the respective color elements). Different digital ID identification functions are imparted to the respective elements in the respective color tanks, the tank of the color for the communication is identified by digital ID, and it is judged whether the communication is enabled or disabled.

FIG. 37 is an explanatory view of a concept by which the digital ID is exchanged between the communication circuit 1150 on the recording apparatus main body side and the solid semiconductor element 1011 by electromagnetic induction. Referring to FIG. 37, first when the digital ID is set to D3h (h is an affix

indicating that D3 is a hexadecimal number) (FIG. 37A),
the communication circuit 1150 converts this to a
binary number "11010011" (FIG. 37B), and a
corresponding electromagnetic induced waveform is
5 formed (FIG. 37C). It is assumed that a digital value
1 is a sine wave of one period, and 0 is an output 0.
When the communication circuit 1150 transmits the
waveform to the solid semiconductor element 1011 by
electromagnetic induction (FIG. 37D), the element in
10 the ink tank is tuned and obtains the similar waveform
with the coil L on the element 1011 (FIG. 37E). The
element 1011 converts the waveform to a digital binary
number string by a comparator circuit, and the like
(FIG. 37F), and can obtain D3h as the digital ID (FIG.
15 37G).

FIG. 38 shows an operation flow for using the
exchange of the digital ID to acquire the tank inside
information of the specific color. First, when the ID
of the response condition of the ink tank for the
20 communication (D3h as the digital ID in this case) is
selected, the communication circuit 1150 converts the
ID to a binary number arrangement by a shift register
(not shown) or the like, converts the arrangement to
the corresponding electromagnetic waveform and
25 transmits the waveform. During the conversion, for
example, the binary number arrangement is multiplied by
the sine wave of the same period in AND gate. The

solid semiconductor element 1011 acquires the same waveform as the transmitted electromagnetic induction waveform with the coil. The waveform is converted to a binary number, and a hexadecimal number is then
5 obtained by a converter disposed in the discrimination means 1016 of the solid semiconductor element 1011.

Subsequently, the discrimination means 1016 compares the acquired ID of hexadecimal number with the identification ID of hexadecimal number pre-stored in
10 the information storing means 1017. When the compared IDs agree with each other, the information subsequent to the ID is received. In case of disagreement, the information is not accepted.

When the information is accepted as described
15 above, the discrimination means 1016 allows the information acquiring means 1015 to acquire the ink tank inside information (e.g., the ink concentration, residual amount, physical property, and the like) as the environmental information of the element 1011 in
20 accordance with the accepted information as shown in FIG. 36. The discrimination means compares the acquired tank inside information with the information stored in the information storing means 1017, and judges whether the acquired tank inside information
25 needs to be transmitted to the outside. The information transmission means 1018 converts the power to the energy for transmitting the tank inside

information to the outside by the command of the discrimination means 1016, and displays/transmits the tank inside information to the outside.

According to the sixth embodiment, the solid semiconductor element having the communication function for a response with the communication protocol using the different ID identification for the respective color ink tanks is disposed. Therefore, similarly as the first embodiment, the element can individually exchange the information with the desired color tank. Moreover, the power for starting the circuit in the element can be supplied in the non-contact manner, and therefore the element can be used even in the ink in which wiring is difficult.

Furthermore, since each color ink tank is identified by the digital ID in the sixth embodiment, a large number of types of tanks can be handled as compared with the constitution of the fifth embodiment.

Additionally, the detection of the ink type stored in the ink tank will be described as one constitution example in which the aforementioned solid semiconductor element is utilized.

FIG. 39 is a block diagram showing the inner constitution of the solid semiconductor element according to one embodiment of the present invention and the exchange with the outside. A solid semiconductor element 91 shown in FIG. 39 comprises:

energy converting means 94 for converting an
electromotive force 92 as the outside energy supplied
to the element 91 from the outside A in the non-contact
manner to a power 93; and light emitting means 95 for
5 using the power obtained by the energy converting means
94 to emit light. The element is disposed in the ink
in the ink tank. The light emitting means 95 is
constituted of the photodiode, and the like.

10 Additionally, the electromagnetic induction, heat,
light, ray, and the like can be applied as the
electromotive force supplied to operate the element.
Moreover, the energy converting means 94 and light
emitting means 95 are preferably formed on the element
surface or in the vicinity of the surface.

15 In this embodiment, when the electromotive force
92 is applied to the element 91 from the outside A, the
energy converting means 94 converts the electromotive
force 92 to the power 93, and the light emitting means
95 uses the power 93 to emit light 96. A strength of
20 the light 96 emitted from the light emitting means 95
is detected by the outside B.

Moreover, in the method of supplying the outside
energy, for use in the ink jet recording apparatus, the
means for supplying the electromotive force to the
25 element as the outside energy may be disposed in the
recovery position, return position, carriage, recording
head, and the like. Additionally, when the apparatus

including the electromotive force supplying means is used, the ink tank inside state can be known without the ink jet recording apparatus. For example, the element may be used for a test purpose in a plant, store, and the like (quality control).

FIG. 40 is a schematic constitution diagram of the ink tank using the solid semiconductor element of the present invention. A solid semiconductor element 1526 shown in FIG. 40 floats in the vicinity of the liquid surface of a raw ink 1522 in an ink tank 1521. An electromotive force is induced by an outside resonance circuit (not shown) disposed outside the ink tank 1521 by electromagnetic induction. The photodiode disposed in the vicinity of the solid semiconductor element 1526 is driven to emit light. The light is transmitted through the ink 1522 and received by an outside light sensor 1550 of the ink tank 1521.

FIG. 41 shows an absorption wavelength of an representative ink (yellow (Y), magenta (M), cyan (C), black (B)). As seen from FIG. 41, in the respective yellow, magenta, cyan, and black color inks, absorption coefficient peaks are dispersed in a wavelength band of 300 to 700 nm. The peak of the absorption coefficient of a yellow ink is about 390 nm, that of a magenta ink is about 500 nm, that of a black ink is about 590 nm, and that of a cyan ink is about 620 nm. Therefore, the light including the wavelength in a range of 300 to 700

nm is emitted from the solid semiconductor element,
transmitted through the ink, and received by the light
sensor 1550 (see FIG. 40) disposed outside the ink
tank. Then, the most absorbed wavelength is detected,
5 and the color of the ink through which the light is
transmitted can be identified.

Moreover, as seen from FIG. 41, the respective
yellow, magenta, cyan and black inks are clearly
different from each other in the absorption coefficient
10 in a wavelength of 500 nm. For the absorption
coefficient of the respective color inks in the
wavelength of 500 nm, magenta has about 80%, black
about 50%, yellow about 20%, and cyan about 5%.
Therefore, the ratio of the strength of the ink
15 transmitted light (transmittance) to the strength of
light emitted by the solid semiconductor element with
respect to the light having the wavelength of 500 nm is
detected, and therefore the color of the ink through
which the light is transmitted can be identified.

20 Additionally, in any case, when one type of the
solid semiconductor element is disposed in the
different ink tanks, a plurality of ink types can be
distinguished.

Moreover, in the ink jet recording apparatus, a
25 plurality of respective ink tanks are attached to
predetermined positions in accordance with the ink type
contained in each ink tank. This constitution may

include means for issuing a warning to the user when the light sensor 1550 having received the light transmitted through the ink in the ink tank detects that the ink tank is attached to an inappropriate position. In this case, examples of the warning means include light emitting means such as a lamp, sounding means such as a buzzer, and the like. The user can be informed by the warning of the warning means that the ink tank is attached to the incorrect position, and can again attach the ink tank to the original position.

Alternatively, the ink jet recording apparatus may include control means for controlling the recording head with the ink supplied thereto from the attached ink tank in accordance with the ink type, when the light sensor having received the light transmitted through the ink in the ink tank detects the attachment of the ink tank to the inappropriate position. In this case, even when the user attaches the ink tank to the wrong position, an image is automatically and appropriately recorded. Therefore, the user does not have to pay attention to the attachment position of the ink tank.

As described above, the solid semiconductor element of the present invention includes the energy converting means for converting the energy from the outside to the different type of energy, and light emitting means for emitting light by the energy

converted by the energy converting means. Therefore,
the light emitted from the solid semiconductor element
is transmitted through the ink, the strength of the
transmitted light in the certain wavelength is
5 detected, and thereby the ink type can be identified.

According to the present invention, the solid
semiconductor element has a communication function of
acquiring the environmental information and
transmitting the information to the outside, only when
10 the signal of the electromagnetic wave from the outside
meets the predetermined response condition. Therefore,
the environmental information for each element can
independently be obtained. Moreover, since the
information can three-dimensionally be
15 acquired/transmitted, as compared with the use of the
planar semiconductor element, little restriction is
imposed on the information transmission direction.
Therefore, the environmental information can
efficiently be acquired and transmitted to the outside.

Moreover, when at least one solid semiconductor el
ement is disposed in the ink tank, the information
about the ink contained in the ink tank, pressure in
the tank, and the like can be transmitted, for example,
to the ink jet recording apparatus disposed outside in
25 real time. This is advantageous in controlling the
negative pressure amount in the tank which changes with
the ink consumption every moment, and in stabilizing

the ink ejection.

Particularly when the respective solid semiconductor elements are disposed in a plurality of ink tanks, and only when the signal of the received electromagnetic wave meets the predetermined response condition, the information is acquired in response to the received signal. The discriminated result of comparison with the stored information can be transmitted to the outside together with the acquired information. When the response condition is changed for each tank, the information for each ink tank can independently be obtained. Therefore, the user can replace the ink tank in which the ink is used up without any mistake.

Furthermore, the power for operating the solid semiconductor element is supplied to the element in the non-contact manner. In this constitution, it is unnecessary to dispose the power source for starting the element in the ink tank, or to connect the power supplying wiring to the element. The element can be used in the place where it is difficult to directly connect the wiring to the outside. Moreover, since the element functions in the vicinity of the tank in the non-contact manner, the element can handle a plurality of colors in one position. Moreover, the information can be transmitted even during printing.

For example, the conductor coil of the oscillation

circuit is wound around the outer surface of the solid semiconductor element, and the power is generated in the conductor coil by electromagnetic induction with the outside resonance circuit, so that the power can be supplied to the element in the non-contact manner.

In this case, since the coil is wound around the element outer surface, the size of inductance of the coil changes in accordance with the ink residual amount, ink concentration, and ink pH in the ink tank. Therefore, since the oscillation circuit can change the oscillation frequency in accordance with the inductance change, the ink residual amount in the ink tank, and the like can also be detected based on the changed oscillation frequency.

Moreover, since the solid semiconductor element has the hollow portion for floating in the liquid and the gravity center of the element is positioned below the center of the element, for example, the recording head and ink tank mounted on the ink jet recording apparatus serially operate. Even when the ink in the ink tank vertically and horizontally rocks, the element floats steadily in the ink in the ink tank, and the information about the ink, pressure in the tank, and the like can precisely be detected. Additionally, the coil of the oscillation circuit formed on the element is held in the stable position with respect to the coil of the outside resonance circuit, and stable

bidirectional communication is also constantly enabled.

A constitution in which the solid semiconductor element is utilized as inner pressure adjustment means of the ink tank will next be described.

5 (Seventh Embodiment)

A seventh embodiment of the ink tank of the present invention will next be described. Here, in a constitution example, the ink can be supplied to the outside via the ink supply port of an ink tank having a double chamber structure as shown in FIG. 6 with high reliability.

In the ink tank having the double chamber structure shown in FIG. 6, as described above, while the ink is supplied via the ink supply port 53, first the ink is isotropically consumed from the negative pressure generating member of the negative pressure generating chamber 51 with respect to the ink supply port 53. When the ink surface reaches the connection path 50b, the atmosphere having entered the negative pressure generation chamber 51 flows into the ink chamber 52 via the connection path 50b. The corresponding amount of ink is introduced into the negative pressure generation chamber 51 from the ink chamber 52, and the ink in the ink chamber 52 is consumed instead of consuming the ink in the negative pressure generating member. Since the ink surface hardly changes in the negative pressure generating

member in this state (hereinafter referred to also as
"during gas-liquid exchange"), the negative pressure
amount becomes constant with respect to the ink jet
head, and the ink jet head can constantly be operated
5 with a stable ejection amount. However, when the ink
consumption amount from the ink supply port 53 is
larger than the ink supply amount to the negative
pressure generation chamber 51 from the ink chamber 52
during gas-liquid exchange, an ink path between the ink
10 chamber 52 and the ink supply port 53 of the negative
pressure generation chamber 51 is interrupted, or the
negative pressure generation chamber 51 cannot be
refilled with a sufficient amount of ink in some case.
This problem is solved by changing the material of the
15 negative pressure generating member around the ink
supply port 53 to a material having an ink absorption
force higher than that of a place other than the
periphery of the ink supply port 53 (e.g., PP pressed
material). However, in this measure, it is impossible
20 to expect the occurrence of the problem and momentarily
(digitally) handle the problem. Therefore, there is a
demand for a function of momentarily handling the
problem when the occurrence of the problem is expected.
Therefore, an ink tank having the double chamber
25 structure similar to that of FIG. 6 and having such
inventive function is proposed here.

FIG. 42 is a schematic sectional view showing the

seventh embodiment of the ink tank of the present invention. In the ink tank having the double chamber structure (similarly as FIG. 6) shown in FIG. 42, a solid semiconductor element 1004 (first monitor means) having a pressure sensor (pressure detecting means) for detecting the pressure fluctuation is disposed in a negative pressure generation chamber 1001. A solid semiconductor element 1005 (flow rate adjustment apparatus) having an open/close valve is disposed in a connection path 1050b, receives a pressure signal from the solid semiconductor element 1004, and adjusts a flow rate of connection path 1050b by the open/close valve. Additionally, the solid semiconductor element 1004 needs to be disposed on a limit line at which ink shortage occurs (gas-liquid interface shown by a dotted line in FIG. 42) in order to prevent the ink shortage beforehand. Reference numeral 1010a denote a partition wall.

Moreover, the first or second embodiment (constitution of FIG. 3 or FIG. 11) can be applied to the solid semiconductor element 1004. In this case, the information acquiring means in the element 1004 is a pressure sensor. On the other hand, the solid semiconductor element 1005 can be constituted by replacing the information transmission means of the second embodiment (constitution of FIG. 11) with the open/close valve and omitting the information acquiring

means. The solid semiconductor element of the second embodiment is utilized as an open/close valve apparatus disposed in the connection path 1050b in this manner.

However, the valve apparatus is not limited to the
5 solid semiconductor element, as long as the valve apparatus can adjust the flow rate of the connection path in the non-contact manner without any power source in the present invention.

Furthermore, a solid semiconductor element 1006
10 (second monitor means) having control means for detecting the ink residual amount and fully opening the open/close valve of the element 1005 when the amount drops to a given amount level is floated on the ink surface in the ink chamber 1002 if necessary. The
15 method of detecting the ink residual amount and generating the buoyancy by the solid semiconductor element 1006 can be the same as that of the first embodiment.

Furthermore, it is considered that the solid
20 semiconductor elements 1004, 1005, 1006 are started by the induced electromotive force described with reference to FIG. 5.

An ink supply operation by the ink tank of the seventh embodiment will next be described.

25 Referring to FIG. 42, the liquid surface of the negative pressure generation chamber 1001 drops to the limit line (dotted line of FIG. 42) below which an ink

path is possibly interrupted during the gas-liquid exchange, and then the solid semiconductor element 1004 moves above the liquid surface and is exposed to the atmosphere. A state in which the liquid is present in the negative pressure generating member around the element 1004 changes to a state in which the liquid is eliminated, and then the pressure fluctuation is caused. The pressure sensor of the element detects the pressure fluctuation, and the state in which the ink path to an ink supply port 1003 from the ink chamber 1002 is interrupted can be detected beforehand. Subsequently, the solid semiconductor element 1004 transmits pressure fluctuation information obtained by the pressure sensor to the solid semiconductor element 1005 of the connection path 1050b.

The solid semiconductor element 1005 receives the pressure fluctuation information from the element 1004, and controls the open/close valve in accordance with the pressure fluctuation information. That is, when the liquid surface of the negative pressure generation chamber 1001 drops to the limit line having a possibility of occurrence of ink path interruption, the open/close valve of the element 1005 of the connection path 1050b is further opened, and the ink supply amount to the negative pressure generation chamber 1001 from the ink chamber 1002 is increased. Moreover, the pressure value of the periphery of the element 1004 is

obtained by the pressure sensor, and it can be judged by the value that the liquid surface returns to the state having no occurrence of ink path interruption.

In this case, the open/close valve of the solid

5 semiconductor element 1005 of the connection path 1050b is closed, and the normal flow rate is obtained.

As described above, in the ink tank having the double chamber structure equal to that of FIG. 3, the function of detecting the possibility of interruption of the ink path to the ink supply port 1003 of the
10 negative pressure generation chamber 1001 from the ink chamber 1002 and momentarily preventing the interruption can be disposed.

Additionally, when the solid semiconductor element
15 1006 is disposed in the ink chamber 1002, the solid semiconductor element 1005 receives the ink residual amount information in the ink chamber 1002 obtained by the solid semiconductor element 1006, and controls and fully opens the open/close valve upon discriminating
20 the ink residual amount of the given amount level or less. Thereby, even when the ink residual amount in the ink chamber 1002 decreases, the sufficient supply amount to the negative pressure generation chamber 1001 can be secured. There can be provided the double
25 chamber structure tank with a higher reliability of ink supply.

The detection of the ink residual amount in the

ink chamber 1002 by the solid semiconductor element 1006 is not limited to the method of utilizing the change of the amplitude value in the resonance frequency range in accordance with the distance between the element and the outside resonance circuit as described in the first embodiment. That is, another method may comprise: disposing the pressure sensor for detecting the pressure of the ink chamber 1002 in the solid semiconductor element 1006; detecting an initial pressure P_0 in the ink chamber 1002 before the liquid is consumed in the ink chamber 1002 and pressure P of a certain point at which the liquid of the ink chamber 1002 is consumed, and obtaining a pressure loss h (see FIG. 42); and transmitting the information of pressure loss h to the solid semiconductor element 1005. The pressure loss h is obtained by $h = (P_0 - P) / \rho g$ (here, ρg denotes the specific weight of the solid semiconductor element). An upper limit value of the pressure loss is set in accordance with respective recording head specifications (e.g., nozzle number, ejection amount, drive frequency, size between the ink tank and the recording head ink supply port, and the like). When the upper limit value is exceeded during use of the recording head, an emergency signal is transmitted to the recording head and recording apparatus from the solid semiconductor element of the present invention. Thereby, the drive signal for controlling the image

data and recording head is stopped from being transferred to the recording head from the recording apparatus, and thereby the image can be prevented from being deteriorated because of ink supply shortage to the recording head.

<Open/Close Valve>

One concrete structure example of the open/close valve in the seventh embodiment will be described together with manufacturing steps.

FIG. 43 is an explanatory view of one example of the solid semiconductor element in which the open/close valve of the seventh embodiment is formed. The element is formed in spherical silicon for use in the ball semiconductor. FIGS. 44A to 44G are explanatory views of the manufacturing steps of the pressure adjustment means shown in FIG. 43. Additionally, FIGS. 43 and 44 show sections taken along the center of the spherical silicon.

As shown in FIG. 43, base electrodes 201 are formed in two opposite portions of the spherical silicon 200. Moreover, an SiN film 206 is formed to surround the spherical silicon 200. The SiN film 206 constitutes movable portions 210, 211 in which portions disposed opposite to the base electrodes 201 are supported in a cantilever manner at an interval from the surface of the spherical silicon 200. Valve electrodes 205 are disposed opposite to the base

electrodes 201 in the respective movable portions 210, 211. Moreover, in a portion extending to the other base electrode 201 from one base electrode 201, the SiN film 206 is formed at an interval from the spherical silicon 200. This portion forms a path 212 in which gas can circulate between one movable portion 210 and the other movable portion 211.

A method of manufacturing the open/close valve shown in FIG. 43 will next be described with reference to FIGS. 44A to 44G.

First, as shown in FIG. 44B, a phospho silicate glass (PSG) film 202 is formed on the whole surface of the spherical silicon 200 shown in FIG. 44A. Additionally, the base electrodes 201 are formed beforehand in two opposite portions symmetrical with each other via the center of the spherical silicon 200, before the PSG film 202 is formed. Thereafter, as shown in FIG. 44C, the photolithography process is used to pattern the PSG film 202 excluding a portion forming the path, in order to form at least an opening 203 for exposing the base electrode 201 in the PSG film 202, and to form the path described later.

Subsequently, as shown in FIG. 44D, a Cu film 204 is formed to coat the base electrode 201 and PSG film 202 by a metal CVD process, and removed leaving upper and peripheral portions of the base electrode 201. Thereafter, as shown in FIG. 44E, the valve electrode

205 is formed in a portion which is to form the movable portion on the Cu film 204. Furthermore, PECVD process is used to form an SiN film 206 on the whole periphery of the spherical silicon 200, so that the PSG film 202, 5 Cu film 204 and valve electrode 205 are coated.

Furthermore, as shown in FIG. 44F, the SiN film 206 is patterned in a movable portion shape. A schematic plan view of the element in this stage is shown in FIG. 45. The SiN film 206 is patterned, and 10 as shown in FIG. 45, radial slits 206a are formed in the Cu film 204 on the SiN film 206. Subsequently, the Cu film 204 and PSG film 202 are appropriately dissolved by a solvent and removed. Thereby, as shown in FIG. 44G, the solid semiconductor element is 15 obtained. In the element, a plurality of movable portions 210, 211 acting as valves are disposed in two upper and lower portions, and supported at an interval from the spherical silicon 200. Moreover, a space between the upper movable portion 210 and the spherical silicon 200 is connected to a space between the lower 20 movable portion 211 and the spherical silicon 200 via a plurality of paths 212.

When the solid semiconductor element is disposed in the ink tank connection path 1050b shown in FIG. 42, 25 one movable portion 210 is positioned on the ink chamber 1002 side of the ink tank shown in FIG. 42, and the other movable portion 211 is positioned on the

negative pressure generation chamber 1001 side of the ink tank of FIG. 42.

5 A method of adjusting the ink supply amount in the ink tank with the solid semiconductor element having the open/close valve attached thereto will next be described with reference to FIGS. 43, 46 and 47.

FIG. 46 is an equivalent circuit diagram of an electric constitution of the open/close valve shown in FIG. 43. As clearly seen from FIG. 46, a capacitor C
10 is constituted between the valve electrode (VE) and base electrode (BE) disposed opposite to each other.

Moreover, FIG. 47 is a timing chart of one example of an applied signal to the valve electrode (VE) and base electrode (BE) in the pressure adjustment means
15 shown in FIG. 46. In FIG. 47, C denotes close, and O denotes open.

First, the base electrode 201 and valve electrode 205 are set to GND level. Subsequently, a high level signal is applied to the base electrode 201, and
20 further to the valve electrode 205. Thereby, an electrostatic attracting force acts between the valve electrode 205 and base electrode 201. Since the valve electrode 205 is attracted to the base electrode 201, as a result, the movable portions 210, 211 disposed in
25 opposite ends of the path 212 are displaced toward the spherical silicon 200 to contact the spherical silicon 200, and the opposite ends of the path 212 are closed

excluding gaps formed by the slits 206a. When the high level signal is applied to all the valve electrodes 205 of the movable portions 210, 211 in the opposite ends of the path 212, outlet/inlet ports of all the paths 212 are minimized.

This state is regarded as an initial state. When the flow rate is increased, a low level signal is applied to the valve electrodes 205 of the movable portions 210, 211 in the opposite ends of the desired number of paths 212. Thereby, the movable portions 210, 211 are detached from the spherical silicon 200, and the outlet/inlet ports of the path 212 largely open. The flow rate can be adjusted in accordance with the number of open paths. Moreover, when the flow rate is again reduced, the high level signal is applied again to the valve electrode 205 to displace the movable portions 210, 21 and close the paths 212. Even in this case, the flow rate to be reduced can be adjusted by the number of closed paths.

As described above, according to the present invention, there is provided the double chamber structure liquid container in which a closed liquid container chamber is connected to an absorber container chamber partially connected to the atmosphere, via the connection path in the bottom surface of the container, and the supply port to the liquid ejection head is disposed in the absorber container chamber. In the

container, at least one element in which the function
of acquiring the information about the liquid (ink) and
function of transmitting the acquired information to
the outside are formed is disposed. The information
5 about the liquid can efficiently be acquired and
transmitted to the outside. Particularly, the driving
of the recording apparatus, ink supply amount, and the
like are controlled based on the information acquired
by the solid semiconductor element, and high-quality
10 recording can be achieved.